

Safety Data Sheet

24 Mix standard solution

Version : V2.0.0.1

Report No. : BWB2541-2016-MSDS-US

Creation Date : 2025/10/11

Revision Date : -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1 Identification

Product identifier

Product Name	24 Mix standard solution
Cat No.	BWB2541-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

Emergency phone number

Emergency phone number	010-58103678
------------------------	--------------

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Skin corrosion/irritation	Category 1C
Serious eye damage/irritation	Category 1
Acute Toxicity - Inhalation	Category 1

Label elements

Hazard pictograms	 
Signal word	Danger

Hazard statements

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled

Precautionary statements

◆ Prevention

P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P271	Use only outdoors or with adequate ventilation.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P284	In case of inadequate ventilation wear respiratory protection.

◆ Response

P320	Specific treatment is urgent (see related instructions on the label).
P321	Specific treatment (see related instructions on the label).
P363	Wash contaminated clothing before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

◆ Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

◆ Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
-------------	---

Other hazards

	Not applicable.
--	-----------------

Hazard description

◆ Physical and chemical hazards

	No information available
--	--------------------------

◆ Health hazards

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the product during the course of normal handling, may produce severely toxic effects; these may be fatal. Corrosive product can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage.
Ingestion	Accidental ingestion of the product may be harmful to the health of the individual.
Skin Contact	The product can cause severe skin burns following direct contact with the skin.
Eye	The product can produce severe chemical burns to the eye following direct contact. If timely and appropriate treatment is not available may cause permanent blindness.

◆ Environmental hazards

Please refer to 12th chapter of SDS.

3 Composition/information on ingredients

Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Water	7732-18-5	231-791-2	87.74
Nitric acid	7697-37-2	231-714-2	10
Aluminium	7429-90-5	231-072-3	0.094
Arsenic	7440-38-2	231-148-6	0.094
Boron	7440-42-8	231-151-2	0.094
Barium	7440-39-3	231-149-1	0.094
Beryllium	7440-41-7	231-150-7	0.094
Bismuth	7440-69-9	231-177-4	0.094
Calcium	7440-70-2	231-179-5	0.094
Cadmium	7440-43-9	231-152-8	0.094
Cobalt	7440-48-4	231-158-0	0.094
Chromium	7440-47-3	231-157-5	0.094
Copper	7440-50-8	231-159-6	0.094
Iron	7439-89-6	231-096-4	0.094
Potassium	7440-09-7	231-119-8	0.094
Lithium	7439-93-2	231-102-5	0.094
Magnesium	7439-95-4	231-104-6	0.094
Manganese	7439-96-5	231-105-1	0.094
Sodium	7440-23-5	231-132-9	0.094
Nickel	7440-02-0	231-111-4	0.094
Phosphorus	7723-14-0	231-768-7	0.094
Lead	7439-92-1	231-100-4	0.0943
Selenium	7782-49-2	231-957-4	0.0943
Strontium	7440-24-6	231-133-4	0.0943
Vanadium	7440-62-2	231-171-1	0.0943
Zinc	7440-66-6	231-175-3	0.0943

4 First-aid measures

Description of first aid measures

General advice

Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Skin contact	Take off contaminated clothing and shoes immediately. Wash off with plenty of soap and water for at least 15 minutes and consult a physician if feel uncomfortable.
Ingestion	Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

| Most important symptoms/effects, acute and delayed

1	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
---	--

| Indication of any immediate medical attention and special treatment needed

1	Treat symptomatically.
2	Symptoms may be delayed.

5 Fire-fighting measures

| Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ or water spray; Large fire: dry chemical, CO ₂ , alcohol-resistant foam or water spray; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Do not get water inside containers.
Unsuitable extinguishing media	No information available.

| Specific hazards arising from the substance or mixture

1	Fire may produce irritating, poisonous or corrosive gases.
2	Development of hazardous combustion gases or vapor possible in the event of fire.
3	May expansion or decompose explosively when heated or involved in fire.

| Special protective equipment and precautions for fire-fighters

1	As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
2	Fight fire from a safe distance, with adequate cover.
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

| Personal precautions, protective equipment and emergency procedures

1	Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
2	Do not touch or walk through spilled material.
3	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
4	Use personal protective equipment, do not breathe gas/mist/vapour/spray.
5	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
---	---

Environmental precautions

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

1	Do not touch or cross spills.
2	It is recommended that emergency personnel wear a self-contained breathing apparatus with positive pressure and wear anti-corrosion clothing.
3	Transfer to a tank truck or special collector with a corrosion-resistant pump.
4	Do not touch broken containers and spills before putting on appropriate protective clothing.
5	Cut off the source of the leak as much as possible.
6	Keep leaks in a ventilated place.
7	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
8	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
9	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.

7 Handling and storage

Precautions for safe handling

1	Handling is performed in a well ventilated place.
2	Wear suitable protective equipment.
3	Avoid contact with skin and eyes.
4	Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

8 Exposure controls/personal protection

Control parameters

◆ Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m ³	ppm	mg/m ³
Nitric acid	Japan - JSOH(2024–2025)	2	5.2	-	-
	Permissible exposure standards for workers in the workplace	2	5.2	4	10.4
	Australia	2	5.2	4	10

	Canada - Ontario	2	-	4	-
	European Union	-	-	1	2.6
	New Zealand	2	5.2	4	10
Aluminium	Japan - JSOH(2024–2025)	-	0.5(respirable dust)	-	-
	Japan - JSOH(2024–2025)	-	2(total dust)	-	-
	Permissible exposure standards for workers in the workplace	-	5(respirable dust)	-	10(respirable dust)
	Australia	-	5(powder, pyrophoric)	-	-
	Canada - Ontario	1	-	-	-
	New Zealand	-	5(pyrophoric powder)	-	-
Arsenic	Japan - JSOH(2024–2025)	-	0.003(individual excess lifetime risk of cancer 10^{-3})	-	-
	Permissible exposure standards for workers in the workplace	-	0.01(as As)	-	0.03(as As)
	Australia	-	0.05	-	-
	Canada - Ontario	-	0.01	-	0.05
	New Zealand	-	0.001	-	-
	USA - ACGIH	-	0.01	-	-
Boron	Germany (DFG)	-	0.75	-	0.75
Barium	Permissible exposure standards for workers in the workplace	-	0.5	-	1.5
	Australia	-	0.5	-	-
	Canada - Ontario	-	0.5	-	-
	European Union	-	0.5	-	-
	New Zealand	-	0.5	-	-
	USA - ACGIH	-	0.5	-	-
Beryllium	Japan - JSOH(2024–2025)	-	0.002	-	-
	Permissible exposure standards for workers in the workplace	-	0.002(as Be)	-	0.006(as Be)
	Australia	-	0.002	-	-

	Canada - Ontario	-	0.002	-	0.01
	European Union	-	0.0002	-	-
	New Zealand	-	0.0002	-	-
Cadmium	Japan - JSOH(2024–2025)	-	0.05	-	-
	Permissible exposure standards for workers in the workplace	-	0.05(as Cd)	-	0.15(as Cd)
	Australia	-	0.01	-	-
	Canada - Ontario	-	0.01(inhalable fraction)	-	-
	European Union	-	0.001	-	-
	New Zealand	-	0.004	-	-
Cobalt	Japan - JSOH(2024–2025)	-	0.05	-	-
	Permissible exposure standards for workers in the workplace	-	0.05(dust and fume)	-	0.15(dust and fume)
	Australia	-	0.05	-	-
	Canada - Ontario	-	0.02	-	-
	New Zealand	-	0.02	-	-
	USA - ACGIH	-	0.02(inhalable fraction)	-	-
Chromium	Japan - JSOH(2024–2025)	-	0.5	-	-
	Permissible exposure standards for workers in the workplace	-	1	-	2
	Australia	-	0.5	-	-
	Canada - Ontario	-	0.5	-	-
	European Union	-	2	-	-
	New Zealand	-	0.5	-	-
Copper	Permissible exposure standards for workers in the workplace	-	1(dust and mist)	-	2(dust and mist)
	Permissible exposure standards for workers in the workplace	-	0.2(fume)	-	0.6(fume)
	Australia	-	0.2(fume, respirable)	-	-






			fraction)		
	Canada - Ontario	-	0.2(fume, respirable fraction)	-	-
	New Zealand	-	0.01	-	-
	USA - ACGIH	-	1(dust and mist)	-	-
Lithium	Germany (AGS)	-	0.2	-	0.2
	Germany (DFG)	-	0.2	-	0.2
	Sweden	-	-	-	0.02
	Switzerland	-	0.2	-	0.2
Manganese	Japan - JSOH(2024–2025)	-	0.02(respirable particles, as Mn)	-	-
	Japan - JSOH(2024–2025)	-	0.1(total particulate, as Mn)	-	-
	Permissible exposure standards for workers in the workplace	-	1(fume)	-	2(fume)
	Australia	-	1	-	-
	Canada - Ontario	-	0.2	-	-
	European Union	-	0.2	-	-
Nickel	Japan - JSOH(2024–2025)	-	1	-	-
	Permissible exposure standards for workers in the workplace	-	1	-	2
	Australia	-	1	-	-
	Canada - Ontario	-	1	-	-
	New Zealand	-	0.005	-	-
	USA - ACGIH	-	1.5(inhalable fraction)	-	-
Phosphorus	Japan - JSOH(2024–2025)	-	0.1	-	-
	Permissible exposure standards for workers in the workplace	-	0.1	-	0.3
	Australia	-	0.1	-	-
	New Zealand	-	0.1	-	-
	USA - NIOSH	-	0.1	-	-
	USA - OSHA	-	0.1	-	-
Lead	Japan -	-	0.03(as Pb)	-	-

	JSOH(2024–2025)				
	Permissible exposure standards for workers in the workplace	-	0.05	-	0.15
	Australia	-	0.05	-	-
	Canada - Ontario	-	0.05	-	-
	European Union	-	0.15	-	-
	New Zealand	-	0.05	-	-
Selenium	Japan - JSOH(2024–2025)	-	0.1	-	-
	Permissible exposure standards for workers in the workplace	-	0.2(as Se)	-	0.6(as Se)
	Australia	-	0.1	-	-
	Canada - Ontario	-	0.2	-	-
	New Zealand	-	0.1	-	-
	USA - ACGIH	-	0.2	-	-
Vanadium	Australia	-	0.05	-	-
	New Zealand	-	0.05	-	-
	USA - OSHA	-	-	0.1	0.5
	Austria	-	0.5(inhalable aerosol)	-	1(inhalable aerosol)
	Germany (DFG)	-	0.005	-	0.01
	Latvia	-	1	-	-
Zinc	Germany (DFG)	-	2	-	4
	Switzerland	-	0.1(respirable aerosol)	-	0.4(respirable aerosol)

Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

Personal protection equipment

General requirement	    
Eye protection	Must wear appropriate anti-corrosion goggles.
Hand protection	Must wear acid and alkali resistant chemical protective gloves.
Respiratory protection	Must wear appropriate personal dust proof gas mask.

Skin and body protection

Must wear acid and alkali resistant chemical protective clothing.

9 Physical and chemical properties and safety characteristics**Physical and chemical properties**

Appearance (physical state, color, etc.)	Clear, colorless liquid
Odor	No information available
Odor threshold	No information available
pH	< 1 (Nitric acid)
Melting point/freezing point(°C)	-41.6 (Nitric acid)
Initial boiling point and boiling range(°C)	121 (Nitric acid)
Flash point(Closed cup, °C)	No information available
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[% (v/v)]	Upper limit : No information available ; Lower limit : No information available
Vapor pressure	6.4kPa (20°C ,Nitric acid)
Vapor density(Air = 1)	2.2 (Nitric acid)
Relative density(Water=1)	1.4 (Nitric acid)
Solubility	500000mg/L (20 °C,Nitric acid)
n-octanol/water partition coefficient	-0.21 (Nitric acid)
Auto-ignition temperature(°C)	No information available
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available

10 Stability and reactivity**Stability and reactivity**

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions	In contact with active metals (alkali metals, Na, Ca etc.) causes a reaction and release hydrogen. Ultrafine powder will self-ignite in the air at room temperature. Mixtures with metallic acetylene, when heated, cause a fire or incandescence. May burn continuously in carbon dioxide. Reacts severely with halogens, interhalogens or other strong oxidants, or causes a fire. May be oxidized quickly when exposed to air.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Alkali, sodium, calcium, and other active metal, halogen, metal oxide, nonmetal oxide, acyl halide and metal phosphide. Oxidants, halogen, interhalogen and mercury. Metal acetylide, halogen, interhalogen, halogen oxides, nitric acid, nitrous oxide, nitrates, nitrites, halogen oxyacid salts, chromates, permanganates, inorganic peroxides, metal oxides and peroxyformic acid. Water, carbon dioxide, oxidants, halogen, interhalogen and mercury. Halogen, interhalogen, strong oxidant, water and acids. Water, carbon dioxide, halocarbon, halogen, interhalogen, metal halide, non-metal oxides, acids, mercury and

	hydrazine.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 Toxicological information

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Manganese	9000mg/kg(Rat)	No information available	No information available
Boron	650mg/kg(Rat)	No information available	No information available
Bismuth	5000mg/kg(Rat)	No information available	No information available
Arsenic	763mg/kg(Rat)	No information available	No information available
Cobalt	6171mg/kg(Rat)	No information available	No information available
Cadmium	2330mg/kg(Rat)	No information available	No information available
Iron	30000mg/kg(Rat)	No information available	No information available
Selenium	6700mg/kg(Rat)	No information available	5.67mg/L(Rat)
Phosphorus	3.03mg/kg(Rat)	No information available	No information available

Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Water	Not Listed	Not Listed	Not Listed
Nitric acid	Not Listed	Not Listed	Not Listed
Aluminium	Not Listed	Not Listed	Not Listed
Arsenic	Category 1	Category K	Listed
Boron	Not Listed	Not Listed	Not Listed
Barium	Not Listed	Not Listed	Not Listed
Beryllium	Category 1	Category K	Not Listed
Bismuth	Not Listed	Not Listed	Not Listed
Calcium	Not Listed	Not Listed	Not Listed
Cadmium	Category 1	Category K	Listed
Cobalt	Category 2A	Category R	Not Listed
Chromium	Category 3	Not Listed	Not Listed
Copper	Not Listed	Not Listed	Not Listed
Iron	Not Listed	Not Listed	Not Listed
Potassium	Not Listed	Not Listed	Not Listed
Lithium	Not Listed	Not Listed	Not Listed
Magnesium	Not Listed	Not Listed	Not Listed
Manganese	Not Listed	Not Listed	Not Listed
Sodium	Not Listed	Not Listed	Not Listed

Nickel	Category 2B	Category R	Not Listed
Phosphorus	Not Listed	Not Listed	Not Listed
Lead	Category 2B	Category R	Not Listed
Selenium	Category 3	Not Listed	Not Listed
Strontium	Not Listed	Not Listed	Not Listed
Vanadium	Not Listed	Not Listed	Not Listed
Zinc	Not Listed	Not Listed	Not Listed

Others

24 Mix standard solution	
Skin corrosion/irritation	Causes severe skin burns and eye damage(Category 1C)
Serious eye damage/irritation	Causes serious eye damage(Category 1)
Skin sensitization	Based on available data, the classification criteria are not met
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

12 Ecological information

Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Chromium	LC ₅₀ : 40.5mg/L (96h)(Fish)	EC ₅₀ : 0.07mg/L (48h)(Crustaceans)	No information available
Calcium	No information available	EC ₅₀ : 49.1mg/L (48h)(Crustaceans)	No information available
Nickel	LC ₅₀ : 40mg/L (96h)(Fish)	EC ₅₀ : 1mg/L (48h)(Crustaceans)	No information available
Cobalt	LC ₅₀ : 1.5mg/L (96h)(Fish)	No information available	No information available
Phosphorus	LC ₅₀ : 0.006mg/L (96h)(Fish)	EC ₅₀ : 0.14mg/L (48h)(Crustaceans)	No information available
Lead	LC ₅₀ : 2.8mg/L (96h)(Fish)	No information available	No information available
Vanadium	LC ₅₀ : 0.693mg/L (96h)(Fish)	No information available	No information available
Copper	LC ₅₀ : 0.665mg/L (96h)(Fish)	EC ₅₀ : 0.02mg/L (48h)(Crustaceans)	ErC ₅₀ : 7.9mg/L (96h)(Algae)
Manganese	LC ₅₀ : 1800mg/L (96h)(Fish)	EC ₅₀ : 40mg/L (48h)(Crustaceans)	No information available
Bismuth	LC ₅₀ : 100mg/L (96h)(Fish)	EC ₅₀ : > 100mg/L (48h)(Crustaceans)	No information available
Magnesium	LC ₅₀ : 541mg/L (96h)(Fish)	No information available	No information available
Aluminium	LC ₅₀ : 1.55mg/L (96h)(Fish)	No information available	No information available
Strontium	LC ₅₀ : > 40.3mg/L	No information available	ErC ₅₀ : > 43.3mg/L

	(96h)(Fish)		(72h)(Algae)
Arsenic	LC ₅₀ : 12.6mg/L (96h)(Fish)	No information available	ErC ₅₀ : 25.2mg/L (72h)(Algae)
Cadmium	LC ₅₀ : 7.8mg/L (96h)(Fish)	EC ₅₀ : 0.58mg/L (48h)(Crustaceans)	No information available
Lithium	LC ₅₀ : 18mg/L (96h)(Fish)	No information available	No information available
Iron	LC ₅₀ : 1.29mg/L (96h)(Fish)	No information available	No information available
Selenium	LC ₅₀ : 2.06mg/L (96h)(Fish)	No information available	ErC ₅₀ : 96mg/L (96h)(Algae)
Zinc	LC ₅₀ : 2.01mg/L (96h)(Fish)	EC ₅₀ : 1.33mg/L (48h)(Crustaceans)	No information available

Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Strontium	NOEC : ≥41.4mg/L(Fish)	No information available	No information available
Selenium	NOEC : 0.025mg/L(Fish)	No information available	No information available

Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Nickel	Low	Low

Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Nickel	Low	Log Kow=-1.38
Phosphorus	High	BCF=2310000

Mobility in soil

Component	log Koc	Remark
Magnesium	1.12	20 °C
Nickel	1.155	

13 Disposal considerations

Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label	
--------------------	---

IMDG-CODE

UN number	3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard class	None
Packing group	III
Marine pollutant (Yes or no)	No

IATA-DGR

UN number	3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard class	None
Packing group	III

UN-ADR

UN number	3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard class	None
Packing group	III

Transport in bulk according to IMO instruments

- ◆ Transport in bulk according to Annex II of MARPOL and the IBC code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

	Not Available
--	---------------

- ◆ Transport in bulk in accordance with the IGC Code

	Not Available
--	---------------

Others

Precautions for transport	Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.
---------------------------	---

15 Regulatory information

International chemical inventory

Component	A	B	C	D	E	F	G	H	I	J	K	L	M
Water	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Nitric acid	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Aluminium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Arsenic	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Boron	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Barium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Beryllium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Bismuth	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Calcium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Cadmium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Cobalt	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓
Chromium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Copper	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Iron	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Potassium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓
Lithium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Magnesium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Manganese	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Sodium	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓
Nickel	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Phosphorus	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Lead	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓
Selenium	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓
Strontium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Vanadium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Zinc	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓

- [A] China Inventory of Existing Chemical Substances(IECSC)
 [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
 [C] United States Toxic Substances Control Act Inventory(TSCA)
 [D] Canadian Domestic Substances List(DSL)
 [E] New Zealand Inventory of Chemicals(NZIoC)
 [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
 [G] Korea Existing Chemicals Inventory(KECL)
 [H] Australian. Inventory of Industrial Chemical (AIICS)
 [I] Japan Inventory of Existing & New Chemical Substances(ENCS)
 [J] Thailand Existing Chemicals Inventory(TECI)
 [K] Mexico National Inventory of Chemical Substances (INSQ)
 [L] Russia Inventory of Existing Substances(DRAFT)
 [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	B	C
Water	×	×	×
Nitric acid	×	×	×
Aluminium	×	×	×
Arsenic	×	×	×
Boron	×	×	×
Barium	×	×	×
Beryllium	×	×	×
Bismuth	×	×	×
Calcium	×	×	×
Cadmium	×	×	×
Cobalt	×	×	×
Chromium	×	×	×
Copper	×	×	×
Iron	×	×	×
Potassium	×	×	×
Lithium	×	×	×
Magnesium	×	×	×
Manganese	×	×	×
Sodium	×	×	×
Nickel	×	×	×
Phosphorus	×	×	×
Lead	×	×	×
Selenium	×	×	×
Strontium	×	×	×
Vanadium	×	×	×
Zinc	×	×	×

【A】 The Montreal Protocol on Substances that Deplete the Ozone Layer

【B】 Stockholm Convention on Persistent Organic Pollutants (POPs)

【C】 Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

Component	A	B	C	D	E	F	G	H
Water	×	×	×	×	×	×	×	×
Nitric acid	×	✓	✓	✓	✓	✓	✓	×
Aluminium	×	×	×	✓	✓	✓	✓	×
Arsenic	✓	×	✓	✓	✓	✓	✓	×
Boron	×	×	×	×	✓	×	×	×

Barium	×	×	×	✓	✓	✓	✓	×
Beryllium	✓	×	✓	✓	✓	✓	✓	×
Bismuth	×	×	×	×	×	×	×	×
Calcium	×	×	×	✓	✓	✓	✓	×
Cadmium	✓	×	✓	✓	✓	✓	✓	×
Cobalt	✓	✓	×	✓	✓	✓	✓	✓
Chromium	✓	×	✓	✓	✓	✓	✓	×
Copper	×	×	✓	✓	✓	✓	✓	×
Iron	×	×	×	×	×	×	×	×
Potassium	×	×	×	✓	✓	✓	✓	×
Lithium	×	×	×	✓	✓	✓	✓	×
Magnesium	×	×	×	✓	✓	✓	✓	×
Manganese	✓	×	×	✓	✓	✓	✓	×
Sodium	×	×	✓	✓	✓	✓	✓	×
Nickel	✓	✓	✓	✓	✓	✓	✓	✓
Phosphorus	✓	✓	✓	✓	✓	✓	✓	×
Lead	✓	×	✓	✓	✓	✓	✓	×
Selenium	✓	×	✓	✓	✓	✓	✓	×
Strontium	×	×	×	×	✓	×	✓	×
Vanadium	×	×	×	✓	✓	✓	✓	×
Zinc	×	×	✓	✓	✓	✓	✓	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
 [B] US SARA 302- Extremely Hazardous Substance List
 [C] US CERCLA- Hazardous Substances List
 [D] US Massachusetts Right-to-Know Substance List
 [E] US New Jersey Right to Know Hazardous Substance List
 [F] US Pennsylvania Right to Know Hazardous Substance List
 [G] US New York City Right-to-Know Hazardous Substance List
 [H] US California Proposition 65 List

Note:

- “✓” Indicates that the substance included in the regulations.
 “×” No data or not included in the regulations.

16 Other information

Information on revision

Creation Date	2025/10/11
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical SafetyCards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>.
 [2] IARC, website: <http://www.iarc.fr/>.
 [3] OECD: The Global Portal to Information on Chemical Substances, website: <https://www.echemportal.org/echemportal/>.

- [4] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>.
 [5] NLM: ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>.
 [6] EPA: Integrated Risk Information System, website: <http://cfpub.epa.gov/iris/>.
 [7] U.S. Department of Transportation: ERG, website: <http://www.phmsa.dot.gov/hazmat/library/erg>.
 [8] Germany GESTIS-database on hazard substance, website: <http://gestis-en.itrust.de/>.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC _x	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P _{OW}	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS -2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.