Safety Data Sheet

Perchlorate in water

Version: V2.0.0.1

Report No.: BWJ4007-2016-MSDS-US

Creation Date: 2025/09/19

Revision Date: -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

| Product identifier

Product Name	Perchlorate in water
Cat No.	BWJ4007-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

| Emergency phone number

Emorgonov	phone number	010 50102670
Emergency	pnone number	U1U-581U3678

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Oxidizing liquids | Category 1

Label elements

Hazard pictograms



Signal word

Danger

| Hazard statements

H271	May cause fire or explosion; strong oxidiser

Perchlorate in water Version: V2.0.0.1 Revision Date: -

| Precautionary statements

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P220	Keep away from clothing and other combustible materials.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P283	Wear fire resistant or flame retardant clothing.

Response

<u> </u>	
P306+P360	IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty
	of water before removing clothes.
P370+P378	Small fire: water; Large fire: flood fire area with water from a distance; Fire
	involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance
	or use unmanned master stream devices or monitor nozzles. Cool containers with
	flooding quantities of water until well after fire is out.
P371+P380+P375	In case of major fire and large quantities: Evacuate area. Fight fire remotely due
	to the risk of explosion.

Storage

P420	Store separately.
Disposal	

P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.

Other hazards

Not applicable.

| Hazard description

Physical and chemical hazards

Contact with combustible material easily cause fire.
i garage de la companya de la compa

Health hazards

Inhalation of the product may produce adverse health effects or irritation of the
respiratory tract following discomfort.
Accidental ingestion of the product may be harmful to the health of the individual.
Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may
produce systemic injury with harmful effects.
This product may cause temporary discomfort following direct contact with the
eye.

Environmental hazards

Please	refer	to 12th	chapter	of SDS

Composition/information on ingredients

| Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Lithium perchlorate	7791-03-9	232-237-2	0.1

Water	7732-18-5	231-791-2	99.9

4 First-aid measures

Description of first aid measures

becomplied of medical co	
General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Skin contact	Take off contaminated clothing and shoes immediately. Wash off with plenty of soap and water for at least 15 minutes and consult a physician if feel uncomfortable.
Ingestion	Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

| Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

5 Fire-fighting measures

| Extinguishing media

Suitable extinguishing media	Small fire: water; Large fire: flood fire area with water from a distance; Fire
	involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance
	or use unmanned master stream devices or monitor nozzles. Cool containers with
	flooding quantities of water until well after fire is out.
Unsuitable extinguishing media	Small fire: do not use dry chemicals or foams. CO ₂ or Halon?may provide limited
	control.

Specific hazards arising from the substance or mixture

1	Will not burn but increases intensity of fire.
2	Contact with combustibles such as wood, paper, oil or finely divided metal may produce spontaneous combustion or violent decomposition.
3	Has a fire-promoting effect due to release of oxygen.
4	The material may provide sufficient oxygen to make the fire fierce and self sustaining.
5	Smothering action may not be effective for established fire.
6	Development of hazardous combustion gases or vapor possible in the event of fire.
7	May expansion or decompose explosively when heated or involved in fire.

Special protective equipment and precautions for fire-fighters

As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.

Perchlorate in water Version: V2.0.0.1 Revision Date:

- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

- 1 Keep combustibles (wood, paper, oil, etc.) away from spilled material.
- 2 Use personal protective equipment, do not breathe gas/mist/vapour/spray.
- 3 Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
- 4 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

- It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
- 2 In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
- In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
- 4 Collect absorbent material using a clean, non-sparking tool.
- 5 Cover with anti-solvent foam to reduce evaporation.
- 6 Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
- 7 Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
- 8 Cut off the source of the leak as much as possible.
- 9 Keep leaks in a ventilated place.
- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 11 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
- 12 Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
- 13 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7 Handling and storage

Precautions for safe handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.

- 3 Keep away from heat/sparks/open flames/hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

8 Exposure controls/personal protection

| Control parameters

Occupational exposure limit values

Occupational	Exposure	limit
	V	alues

No relevant regulations

| Engineering controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

| Personal protection equipment

General requirement	
Eye protection	Must wear appropriate safety goggles.
Hand protection	Must wear appropriate chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear appropriate chemical protective clothing and chemical resistant shoes.

Physical and chemical properties and safety characteristics

| Physical and chemical properties

i ilyonom ama omonimom propo	
Appearance (physical state,	colorless liquid
color, etc.)	
Odor	No special odor (Lithium perchlorate)
Odor threshold	No information available (Lithium perchlorate)
рН	7 (Neutral) (Lithium perchlorate)
Melting point/freezing point(°C)	236 (Lithium perchlorate)
Initial boiling point and boiling range(°C)	No information available (Lithium perchlorate)
Flash point(Closed cup,°C)	No information available (Lithium perchlorate)
Evaporation rate	No information available (Lithium perchlorate)
Flammability	Not combustible (Lithium perchlorate)
Upper/lower explosive limits[%(v/v)]	Upper limit: No information available (Lithium perchlorate); Lower limit: No information available (Lithium perchlorate)
Vapor pressure	Not applicable (Lithium perchlorate)
Vapor density(Air = 1)	Not applicable (Lithium perchlorate)
Relative density(Water=1)	2.295 (20 °C,Lithium perchlorate)
Solubility	464g/L (20 °C(pH=5.6~5.7),Lithium perchlorate)
n-octanol/water partition coefficient	No information available (Lithium perchlorate)

Auto-ignition temperature(°C)	Not combustible (Lithium perchlorate)
Decomposition temperature(°C)	No information available (Lithium perchlorate)
Kinematic viscosity	Not applicable (Lithium perchlorate)

10 Stability and reactivity

| Stability and reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions	Mixture with metal powders may explode if heated, impact or friction. In contact with active metals (alkali metals, Na, Ca etc.) causes a reaction and release hydrogen.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Metal powder, metal amino compounds, ammonia, ammonium salts, amine, amide, carboxylic acids, phenols, alcohols, carboxylic acid esters, nitriles, sulfuric acid, concentrated nitric acid and phosphoric acid. Alkali, sodium, calcium, and other active metal, halogen, metal oxide, nonmetal oxide, acyl halide and metal phosphide.
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products
products	should not be produced.

11 Toxicological information

Acute toxicity

Acute toxicity	No information available
----------------	--------------------------

Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Lithium perchlorate	Not Listed	Not Listed	Not Listed
Water	Not Listed	Not Listed	Not Listed

Others

Perchlorate in water	
Skin corrosion/irritation	Based on available data, the classification criteria are not met
Serious eye damage/irritation	Based on available data, the classification criteria are not met
Skin sensitization	Based on available data, the classification criteria are not met
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

12 Ecological information

Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Lithium perchlorate	No information available	EC ₅₀ : > 100mg/L (48h)(Crustaceans)	ErC ₅₀ : > 120mg/L (72h)(Algae)

| Chronic aquatic toxicity

Chronic aquatic toxicity	No information available
--------------------------	--------------------------

| Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Lithium perchlorate	High	High

| Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Lithium perchlorate	Low	Log Kow=-4.6296

Mobility in soil

Component	log Koc	Remark
Lithium perchlorate	1.687	

13 Disposal considerations

| Disposal considerations

<u> </u>	
Waste chemicals	Before disposal should refer to the relevant national and local laws and
	regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot
	and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label



| IMDG-CODE

UN number	1479
UN proper shipping name	OXIDIZING SOLID, N.O.S.
Transport hazard class	5.1
Transport subsidiary hazard	None
class	
Packing group	I
Marine pollutant (Yes or no)	No

Perchlorate in water Version : V2.0.0.1 Revision Date : -

IATA-DGR

UN number	1479
UN proper shipping name	OXIDIZING SOLID, N.O.S.
Transport hazard class	5.1
Transport subsidiary hazard	None
class	
Packing group	I

UN-ADR

UN number	1479
UN proper shipping name	OXIDIZING SOLID, N.O.S.
Transport hazard class	5.1
Transport subsidiary hazard	None
class	
Packing group	I

Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

Others

Precautions for transport	Strictly prohibited shipping or transportation with acids, flammable goods, organic
	matter, reducing agents, spontaneous combustion, flammable goods which are
	wet. Transport vehicles should be equipped with the appropriate variety and
	quantity of fire equipment and emergency equipment leakage during transport.
	Before transport, should be preceded by checking whether container integrity,
	sealing. The transport unit must be placarded and marked in accordance with

15 Regulatory information

International chemical inventory

Component	Α	В	С	D	E	F	G	Н	I	J	K	L	M
Lithium perchlorate	√	√	√	√	√	×	√	V	√	×	×	√	√
Water	1	1	1	√	1								

relevant transporting requirements.

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZIoC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- 【G】 Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)

Perchlorate in water Version: V2.0.0.1 Revision Date: -

- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	В	С
Lithium perchlorate	×	×	×
Water	×	×	×

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Lithium perchlorate	×	×	×	×	×	×	×	×
Water	×	×	×	×	×	×	×	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

Note:

- " $\sqrt{}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

16 Other information

Information on revision

Creation Date	2025/09/19
Revision Date	-
Reason for revision	-

Reference

- $[1] \qquad \text{IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.} \\$
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG- CODE	International Maritime Dangerous Goods CODE

MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC_X	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
Pow	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	RespiratoryProtective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.