Safety Data Sheet

N,N-diisopropylethylamine

Version: V2.0.0.1

Report No.: BWJ4841-2016-MSDS-US

Creation Date: 2025/10/09

Revision Date: -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1 Identification

| Product identifier

Product Name	N,N-diisopropylethylamine
Cat No.	BWJ4841-2016
CAS No.	7087-68-5
EC No.	230-392-0
Molecular Formula	C8H19N

Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

| Emergency phone number

Emargana	nhana		040 50402670
Emergency	pnone	number	010-58103678

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Flammable liquids	Category 2
Acute Toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1C
Serious eye damage/irritation	Category 1

Label elements

Hazard pictograms







Not applicable.

| Hazard description

Version: V2.0.0.1 Revision Date: -

Physical and chemical hazards

	Highly	flammable liquids	, its vapor	and air	mixture can form	explosive mixture.
--	--------	-------------------	-------------	---------	------------------	--------------------

Version: V2.0.0.1 Revision Date: -

Health hazards

V Hoalth Hazards	
Inhaled	Corrosive product can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage.
Ingestion	Accidental ingestion of the product may be harmful.
Skin Contact	The product can cause severe skin burns following direct contact with the skin.
Eye	The product can produce severe chemical burns to the eye following direct contact. If timely and appropriate treatment is not available may cause permanent blindness.

Environmental hazards

Please refer to 12th chapter of SDS.

Composition/information on ingredients

| Substance/mixture

Substance

Component	CAS No.	EC No.	Concentration (wt, %)
Ethyldiisopropylamine	7087-68-5	230-392-0	99.5

4 First-aid measures

Description of first aid measures

· ·	
General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Skin contact	Take off contaminated clothing and shoes immediately. Wash off with plenty of soap and water for at least 15 minutes and consult a physician if feel uncomfortable.
Ingestion	Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

| Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

5 Fire-fighting measures

Discharge into the environment must be avoided.

wear anti-static clothing.

2

3

Methods and materials for containment and cleaning up

	in,in-alisopi	оругентугаттігге	version . vz.u.u.1 Revision Date
Ext	inguishing media		
Su	itable extinguishing media	water spray, fog or alcohol-resistar maximum distance or use unmann	ter spray or alcohol-resistant foam; Large fire: nt foam; Fire involving tanks: Fight fire from ed master stream devices or monitor nozzles. ntities of water until well after fire is out.
Unsu	itable extinguishing media	No information available.	
S	pecific hazards arising fro	om the substance or mixture	
1	Will form explosive mixtures	with air.	
2	Fire exposed containers may or vapour concentration.	vent contents through pressure reli	ef valves thereby increasing fire intensity and/
3	Vapours may travel to source	of ignition and flash back.	
4	Liquid and vapour are flamm	able.	
5	Fire may produce irritating, p	oisonous or corrosive gases.	
6	Development of hazardous of	combustion gases or vapor possible	in the event of fire.
7	May expansion or decompos	e explosively when heated or involve	ed in fire.
Spe	ecial protective equipmen	t and precautions for fire-fighte	ers
1		<u> </u>	NIOSH approved or equivalent) and full
2	Fight fire from a safe distance, with adequate cover.		
3	Prevent fire extinguishing water from contaminating surface water or the ground water system.		
6	Accidental release m	easures	
Per	sonal precautions, protec	tive equipment and emergenc	y procedures
1	Avoid breathing vapours and	contacting with skin and eye.	
2	Beware of vapours accumula	ating to form explosive concentration	ns.
3	Vapours can accumulate in l	ow areas.	
4	Emergency personnel wear panti-static clothing. Wear che	•	athing apparatus. Wear protective and
5	Fully encapsulating, vapor pr	otective clothing should be worn for	spills and leaks with no fire.
6	Do not touch or walk through	spilled material.	
7	Do not touch damaged conta	ainers or spilled material unless wear	ring appropriate protective clothing.
8	Use personal protective equi	pment,do not breathe gas/mist/vapo	pur/spray.
9	Ensure adequate ventilation. discharges.	Remove all sources of ignition. Take	e precautionary measures against static
10	Evacuate personnel to safe a	areas. Keep people away from and u	upwind of spill/leak.
Env	vironmental precautions		
1	Prevent further leakage or sp	oillage if safe to do so.	
_	5		

It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and

In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the

In case of small amount of spillage, use clean non sparking tools to collect absorption materials.

4 / 10

Version: V2.0.0.1 Revision Date: -

	N,N-diisopropylethylamine Version: V2.0.0.1 Revision Date: -
	leakage in the restricted space.
4	Collect absorbent material using a clean, non-sparking tool.
5	Cover with anti-solvent foam to reduce evaporation.
6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Do not touch or cross spills.
9	It is recommended that emergency personnel wear a self-contained breathing apparatus with positive pressure and wear anti-corrosion clothing.
10	Transfer to a tank truck or special collector with a corrosion-resistant pump.
11	Do not touch broken containers and spills before putting on appropriate protective clothing.
12	Cut off the source of the leak as much as possible.
13	Keep leaks in a ventilated place.
14	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
15	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
16	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
17	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
7	Handling and storage
Pre	cautions for safe handling
1	Avoid inhalation of vapors.
2	Use only non-sparking tools.
3	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.

- 4 Use explosion proof equipment.
- 5 Handling is performed in a well ventilated place.
- 6 Wear suitable protective equipment.
- 7 Avoid contact with skin and eyes.
- Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/hot surfaces.
- Store away from incompatible materials and foodstuff containers.

Exposure controls/personal protection

| Control parameters

Occupational Exposure limit	No relevant regulations
values	

| Engineering controls

- Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.

3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

Version: V2.0.0.1 Revision Date: -

| Personal protection equipment

General requirement	
Eye protection	Must wear appropriate anti-corrosion goggles.
Hand protection	Must wear acid and alkali resistant chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

9 Physical and chemical properties and safety characteristics

| Physical and chemical properties

Appearance (physical state,	colorless liquid
color, etc.)	
Odor	No information available
Odor threshold	No information available
рН	12.3
Melting point/freezing point(°C)	No information available
Initial boiling point and boiling	128.33 (101.325 kPa)
range(°C)	
Flash point(Closed cup,°C)	10.56
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive	Upper limit: 6.3; Lower limit: 0.7
limits[%(v/v)]	44.051.D. (0000.)
Vapor pressure	14.25hPa (20°C)
Vapor density(Air = 1)	>1
Relative density(Water=1)	0.76 (20°C)
Solubility	Partly miscible with water
n-octanol/water partition	-1.8 (22.5 °C)
coefficient	
Auto-ignition temperature(°C)	240
Decomposition temperature(°C)	No information available
Kinematic viscosity	0.88 mm2/s (20°C)

10 Stability and reactivity

| Stability and reactivity

Claiming and reactivity	
Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous	No information available.
reactions	
Conditions to avoid	Incompatible materials, heat, flame and spark.

Incompatible materials	No information available.
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products
products	should not be produced.

Version: V2.0.0.1 Revision Date: -

11 Toxicological information

Acute toxicity

Acute toxicity	No information available
----------------	--------------------------

| Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Ethyldiisopropylamine	Not Listed	Not Listed	Not Listed

Others

Ethyldiisopropylamine(Component)			
Skin corrosion/irritation	Causes severe skin burns and eye damage(Category 1C)		
Serious eye damage/irritation	Causes serious eye damage(Category 1)		
Skin sensitization	Based on available data, the classification criteria are not met		
Respiratory sensitization	Based on available data, the classification criteria are not met		
Reproductive toxicity	Based on available data, the classification criteria are not met		
STOT-repeated exposure	Based on available data, the classification criteria are not met		
Aspiration hazard	Based on available data, the classification criteria are not met		
Germ cell mutagenicity	Based on available data, the classification criteria are not met		

12 Ecological information

Acute aquatic toxicity

Acute aquatic toxicity	No information available
Acute addatic toxicity	I INO II II OITTI ALIOTT AVAITADIE

| Chronic aquatic toxicity

Chronic aquatic toxicity No information available

| Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Ethyldiisopropylamine	High	High

| Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Ethyldiisopropylamine	Low	Log Kow=2.3471

| Mobility in soil

Component	log Koc	Remark
Ethyldiisopropylamine	3.37	20 ℃

13 Disposal considerations

| Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot
Disposal recommendations	and ignition source of fire. Return to supplier for recycling if possible. Refer to section waste chemicals and contaminated packaging.

Version: V2.0.0.1 Revision Date: -

14 Transport information

Label and Mark

Transporting Label





IMDG-CODE

<u>•</u>	
UN number	2924
UN proper shipping name	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport hazard class	3
Transport subsidiary hazard	8
class	
Packing group	п
Marine pollutant (Yes or no)	No

IATA-DGR

UN number	2924
UN proper shipping name	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport hazard class	3
Transport subsidiary hazard	8
class	
Packing group	п

UN-ADR

UN number	2924
UN proper shipping name	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport hazard class	3
Transport subsidiary hazard	8
class	
Packing group	п

Transport in bulk according to IMO instruments

◆Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

Others

Precautions for transport

Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

Version: V2.0.0.1 Revision Date: -

15 Regulatory information

International chemical inventory

Component	A	В	С	D	E	F	G	Н	I	J	K	L	M
Ethyldiisopropylamine	√	√	√	√	√	×	√	√	√	√	√	√	

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZloC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- **[G]** Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	Α	В	С
Ethyldiisopropylamine	×	×	×

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Ethyldiisopropylamine	×	×	×	×	×	×	×	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List

- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

Note:

- " $\sqrt{}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

16 Other information

Information on revision

Creation Date	2025/10/09
Revision Date	-
Reason for revision	-

Version: V2.0.0.1 Revision Date: -

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG- CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC_X	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
Pow	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.