### **Safety Data Sheet**

# 6 Mix organophosphorus in acetone

Version: V2.0.0.1

Report No.: BWN5456-2016-MSDS-US

Creation Date: 2025/10/13

Revision Date: -



#### \*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1 Identification

### | Product identifier

Product Name	6 Mix organophosphorus in acetone
Cat No.	BWN5456-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

### Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

### Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang
	City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

### | Emergency phone number

Emergency phone number	010-59103679
Emergency phone number	UTU-28TU3878

2 Hazard(s) identification

### Hazard classification according to 29 CFR 1910.1200

Flammable liquids	Category 2
Serious eye damage/irritation	Category 2
Specific target organ toxicity -	Category 3
single exposure; narcotic	
effects	

#### Label elements

**Hazard pictograms** 





o Mix organophosphorus in aceton	e Version : V2.0.0.1 Revision Date :
Signal word	<b>Danger</b>
Hazard statements	
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
Precautionary statements	
<ul><li>Prevention</li></ul>	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P271	Use only outdoors or with adequate ventilation.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
◆ Response	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P370+P378	Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fightire from maximum distance or use unmanned master stream devices or monitor
	nozzles. Cool containers with flooding quantities of water until well after fire is ou
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
◆ Storage	
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
<ul><li>Disposal</li></ul>	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	
	Not applicable.
Honord docerinties	
<ul><li>Hazard description</li><li>Physical and chemical haz</li></ul>	ards
	Highly flammable liquids, its vapor and air mixture can form explosive mixture.
→ Health hazards	· · · · · · · · · · · · · · · · · · ·
Inhaled	Sore throat. Cough. Confusion. Headache. Dizziness. Drowsiness.
IIIIalea	Co. C Cough. Common. Floudation. Dizziness. Diowsiness.

	Unconsciousness.
Ingestion	Nausea. Vomiting. (Further see Inhalation).
Skin Contact	Dry skin.
Eye	Redness. Pain. Blurred vision. Possible corneal damage.
Environmental hazards	
	Please refer to 12th chapter of SDS.

# 3 Composition/information on ingredients

### Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Acetone	67-64-1	200-662-2	99.994
Dichlorvos	62-73-7	200-547-7	0.001
Dimethoate	60-51-5	200-480-3	0.001
Parathion-methyl	298-00-0	206-050-1	0.001
Malathion	121-75-5	204-497-7	0.001
Parathion	56-38-2	200-271-7	0.001
Demeton-S	126-75-0	204-801-8	0.001

# 4 First-aid measures

### Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
Skin contact	Remove contaminated clothes. Rinse and then wash skin with water and soap.
Ingestion	Rinse mouth. Refer for medical attention.
Inhalation	Fresh air, rest. Refer for medical attention.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

### Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

### Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

# 5 Fire-fighting measures

### Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO <sub>2</sub> or alcohol-resistant foam; Large fire:
	alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight

7

	x organio priosprior as in accion	Telsion : V2.0.012 Revision Bate :
Unsu	itable extinguishing media	fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.  Use of water spray when fighting fire may be inefficient.
		Tool or manor opin, men ngiming me may so memerenii
S	pecific hazards arising fro	m the substance or mixture
1	Will form explosive mixtures	with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ or vapour concentration.	
3	Vapours may travel to source	e of ignition and flash back.
4	Liquid and vapour are flamm	able.
5	Development of hazardous combustion gases or vapor possible in the event of fire.	
6	May expansion or decompos	e explosively when heated or involved in fire.
Spe	ecial protective equipmen	t and precautions for fire-fighters
1	As in any fire, wear self-conta	ained breathing apparatus (MSHA/NIOSH approved or equivalent) and full
	protective gear.	
2	Fight fire from a safe distance	<u> </u>
3	Prevent fire extinguishing wa	ter from contaminating surface water or the ground water system.
6	Accidental release mo	easures
Per	sonal precautions, protec	tive equipment and emergency procedures
1	Avoid breathing vapours and	contacting with skin and eye.
2	Beware of vapours accumula	ating to form explosive concentrations.
3	Vapours can accumulate in le	ow areas.
4	Emergency personnel wear panti-static clothing. Wear che	positive pressure self-contained breathing apparatus. Wear protective and emical impermeable gloves.
5	Use personal protective equi	pment,do not breathe gas/mist/vapour/spray.
6	Ensure adequate ventilation. discharges.	Remove all sources of ignition. Take precautionary measures against static
7	Evacuate personnel to safe a	areas. Keep people away from and upwind of spill/leak.
Env	rironmental precautions	
1	Prevent further leakage or sp	pillage if safe to do so.
2	Discharge into the environme	nt must be avoided.
Me	thods and materials for co	ontainment and cleaning up
1	It is recommended that emer wear anti-static clothing.	gency personnel wear positive pressure self-contained breathing apparatus and
2	In case of small amount of sp	oillage, use clean non sparking tools to collect absorption materials.
3	reduce evaporation. Water space	
4		sing a clean, non-sparking tool.
5	Cover with anti-solvent foam	<u> </u>
6	Cover with DRY earth, DRY spreading or contact with rain	sand or other non-combustible material followed with plastic sheet to minimize n.

Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.

Cut off the source of the leak as much as possible.

Version: V2.0.0.1 Revision Date: -

9	Keep leaks in a ventilated place.
10	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
11	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
12	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
13	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

# 7 Handling and storage

## | Precautions for safe handling

1	Avoid inhalation of vapors.
2	Use only non-sparking tools.
3	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
4	Use explosion proof equipment.
5	Handling is performed in a well ventilated place.
6	Wear suitable protective equipment.
7	Avoid contact with skin and eyes.
8	Keep away from heat/sparks/open flames/ hot surfaces.

## Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

# 8 Exposure controls/personal protection

## | Control parameters

Occupational exposure limit values

Component	Component Country/Region		Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m³	ppm	mg/m³	
Acetone	Japan - JSOH(2024–202 5)	200	475	-	-	
	Permissible exposure standards for workers in the workplace	200	475	250	593.75	
	Australia	500	1185	1000	2375	
	Canada - Ontario	250	-	500	-	
	European Union	500	1210	-	-	
	New Zealand	500	1185	1000	2375	
Dichlorvos	Permissible exposure standards for workers in the	0.1	1	0.3	2	

	workplace				
	Australia	0.1	0.9	_	_
	Canada - Ontario	-	0.1	-	-
	New Zealand	0.1	0.9	-	-
	USA - ACGIH	-	0.1(inhalable fraction and vapor)	-	-
	USA - NIOSH	-	1	-	-
Dimethoate	Poland	-	0.2	-	0.6
	Romania	-	7	-	10
Parathion-methyl	Permissible exposure standards for workers in the workplace	-	0.2	-	0.6
	Canada - Ontario	-	0.02	-	-
	USA - ACGIH	-	0.02(inhalable fraction and vapor)	-	-
	USA - NIOSH	-	0.2	-	-
	Austria	-	0.2	-	0.4
	Belgium	-	0.02	-	-
Malathion	Japan - JSOH(2024–202 5)	-	10	-	-
	Permissible exposure standards for workers in the workplace	-	10	-	15
	Australia	-	10	-	-
	Canada - Ontario	-	1	-	-
	New Zealand	-	1	-	-
	USA - ACGIH	-	1(inhalable fraction and vapor)	-	-
Parathion	Japan - JSOH(2024–202 5)	-	0.1	-	-
	Permissible exposure standards for workers in the workplace	-	0.1	-	0.3
	Australia	-	0.1	-	-
	Canada - Ontario	-	0.05	-	-
	USA - ACGIH	-	0.05(inhalable fraction and vapor)	-	-
	USA - NIOSH	-	0.05	-	-

### | Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

Version: V2.0.0.1 Revision Date: -

### | Personal protection equipment

General requirement	
Eye protection	Must wear appropriate safety goggles.
Hand protection	Must wear anti static chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

# 9 Physical and chemical properties and safety characteristics

### | Physical and chemical properties

i nyonan ama onomiaan propo	
Appearance (physical state,	Clear, colorless liquid
color, etc.)	
Odor	No information available
Odor threshold	No information available
рН	No information available
Melting point/freezing point(°C)	-95 ( Acetone )
Initial boiling point and boiling	56 ( Acetone )
range(°C)	
Flash point(Closed cup,°C)	-18 ( Acetone )
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit: 13 ( Acetone ); Lower limit: 2.2 ( Acetone )
Vapor pressure	24kPa ( 20°C,Acetone )
Vapor density(Air = 1)	2.0 ( Acetone )
Relative density(Water=1)	0.8 ( Acetone )
Solubility	Miscible with water ( Acetone )
n-octanol/water partition	-0.24 ( Acetone )
coefficient	
Auto-ignition temperature(°C)	465 ( Acetone )
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available
<u> </u>	

# 10 Stability and reactivity

### | Stability and reactivity

Classify and reactivity			
Reactivity	Contact with incompatible substances can cause decomposition or other		
	chemical reactions.		

Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions	In contact with oxidants may cause a fire or an explosion.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Oxidants, chloroform and bromoform
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products
products	should not be produced.

# 11 Toxicological information

## Acute toxicity

Component	LD <sub>50</sub> (oral)	LD <sub>50</sub> (dermal)	LC <sub>50</sub> (inhalation,4h)
Dichlorvos	57~108mg/kg(Rat)	107mg/kg(Rabbit)	0.015mg/L(Rat)
Parathion	13mg/kg(Rat)	15mg/kg(Rabbit)	0.084mg/L(Rat)
Dimethoate	150mg/kg(Rat)	353mg/kg(Rat)	No information available
Acetone	5800mg/kg(Rat)	> 15800mg/kg(Rabbit)	76mg/L(Rat)
Malathion	2100mg/kg(Rat)	4100mg/kg(Rabbit)	> 5.2mg/L(Rat)
Demeton-S	1.5mg/kg(Rat)	No information available	No information available
Parathion-methyl	14mg/kg(Rat)	300mg/kg(Rabbit)	0.034mg/L(Rat)

## | Carcinogenicity

Component	List of carcinogens by	Report on Carcinogens	OSHA Carcinogen List
	the IARC Monographs	by NTP	
Acetone	Not Listed	Not Listed	Not Listed
Dichlorvos	Category 2B	Not Listed	Not Listed
Dimethoate	Not Listed	Not Listed	Not Listed
Parathion-methyl	Category 3	Not Listed	Not Listed
Malathion	Category 2A	Not Listed	Not Listed
Parathion	Category 2B	Not Listed	Not Listed
Demeton-S	Not Listed	Not Listed	Not Listed

## Others

6 Mix organophosphorus in acetone			
Skin corrosion/irritation	Based on available data, the classification criteria are not met		
Serious eye damage/irritation	Causes serious eye irritation(Category 2)		
Skin sensitization	Based on available data, the classification criteria are not met		
Respiratory sensitization	Based on available data, the classification criteria are not met		
Reproductive toxicity	Based on available data, the classification criteria are not met		
STOT-single exposure	May cause drowsiness or dizziness(Category 3)		
STOT-repeated exposure	Based on available data, the classification criteria are not met		
Aspiration hazard	Based on available data, the classification criteria are not met		
Germ cell mutagenicity	Based on available data, the classification criteria are not met		

# 12 Ecological information

## | Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Dichlorvos	LC <sub>50</sub> : 1.32mg/L (96h)(Fish)	EC <sub>50</sub> : 0.00028mg/L (48h)(Crustaceans)	No information available
Parathion	LC <sub>50</sub> : 1mg/L (96h)(Fish)	EC <sub>50</sub> : 0.001mg/L (48h)(Crustaceans)	No information available
Dimethoate	LC <sub>50</sub> : 7.65mg/L (96h)(Fish)	EC <sub>50</sub> : 0.84mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 37.5mg/L (96h)(Algae)
Acetone	LC <sub>50</sub> : 5540mg/L (96h)(Fish)	EC <sub>50</sub> : 18500mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 7200mg/L (96h)(Algae)
Malathion	LC <sub>50</sub> : 0.28mg/L (96h)(Fish)	EC <sub>50</sub> : 0.00215mg/L (48h)(Crustaceans)	No information available
Parathion-methyl	LC <sub>50</sub> : 5.16mg/L (96h)(Fish)	EC <sub>50</sub> : 0.0026mg/L (48h)(Crustaceans)	ErC <sub>50</sub> : 11mg/L (96h)(Algae)

Version: V2.0.0.1 Revision Date: -

## | Chronic aquatic toxicity

Chronic aquatic toxicity No information available

## | Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Dichlorvos	High	High
Dimethoate	Media(Half-life = 112 days)	Low(Half-life = 0.2 days)
Parathion-methyl	High(Half-life = 360 days)	Low(Half-life = 0.44 days)
Malathion	Media(Half-life = 103 days)	Low(Half-life = 0.41 days)
Parathion	High	High

## | Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Dichlorvos	Low	Log Kow=1.47
Dimethoate	Low	BCF=8
Parathion-methyl	Low	BCF=71
Malathion	Low	BCF=119
Parathion	Low	BCF=400

## | Mobility in soil

Component	log Koc	Remark
Dichlorvos	1.604	
Dimethoate	1.390	
Parathion-methyl	2.718	
Malathion	1.484	

Parathion	3.250	

# 13 Disposal considerations

### | Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

# 14 Transport information

### Label and Mark

Transporting Label



### | IMDG-CODE

UN number	1090
UN proper shipping name	ACETONE
Transport hazard class	3
Transport subsidiary hazard class	None
Packing group	п
Marine pollutant ( Yes or no )	No

#### IATA-DGR

UN number	1090
UN proper shipping name	ACETONE
Transport hazard class	3
Transport subsidiary hazard	None
class	
Packing group	п

## UN-ADR

UN number	1090
UN proper shipping name	ACETONE
Transport hazard class	3
Transport subsidiary hazard	None
class	
Packing group	п

### Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

#### Others

#### **Precautions for transport**

Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

Version: V2.0.0.1 Revision Date: -

# 15 Regulatory information

### International chemical inventory

Component	A	В	С	D	Е	F	G	Н	I	J	K	L	М
Acetone	√	√	√	<b>√</b>	<b>√</b>	<b>V</b>	√	√	√	<b>√</b>	<b>√</b>	<b>V</b>	<b>√</b>
Dichlorvos	√	√	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	√	×	√	×	<b>√</b>	<b>√</b>	<b>√</b>
Dimethoate	√	√	<b>√</b>	×	<b>√</b>	<b>√</b>	√	×	√	×	<b>√</b>	<b>√</b>	√
Parathion-methyl	<b>√</b>	<b>√</b>	×	×	×	<b>V</b>	<b>√</b>	×	×	×	<b>√</b>	<b>√</b>	<b>√</b>
Malathion	1	<b>√</b>	×	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	×	<b>√</b>	×	<b>√</b>	<b>√</b>	<b>√</b>
Parathion	1	<b>√</b>	×	×	×	<b>V</b>	<b>√</b>	×	×	×	<b>√</b>	<b>V</b>	<b>√</b>
Demeton-S	×	<b>√</b>	×	×	×	×	×	×	×	×	×	×	×

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZIoC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

#### List of Chemical Substances under International Conventions

Component	A	В	С
Acetone	×	×	×
Dichlorvos	×	×	×
Dimethoate	×	×	×

Parathion-methyl	×	×	<b>√</b>
Malathion	×	×	×
Parathion	×	×	<b>√</b>
Demeton-S	×	×	×

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

### US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Acetone	×	×	√	<b>√</b>	<b>√</b>	√	<b>√</b>	×
Dichlorvos	√	<b>√</b>						
Dimethoate	×	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	√	√	×
Parathion-methyl	×	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	×
Malathion	×	×	√	<b>√</b>	<b>√</b>	√	√	√
Parathion	√	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	√	<b>√</b>	√
Demeton-S	×	×	×	×	×	×	×	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

#### Note:

- " $\sqrt{\phantom{a}}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

## 16 Other information

#### Information on revision

Creation Date	2025/10/13
Revision Date	-
Reason for revision	-

### Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

#### Abbreviations and acronyms

#### Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.