Safety Data Sheet

12 Mix Chlorobenzenes in Carbon disulfide

Version: V2.0.0.1

Report No.: BWQ8935-2016-MSDS-US

Creation Date: 2025/10/13

Revision Date: -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1 Identification	on
------------------	----

| Product identifier

•	
Product Name	12 Mix Chlorobenzenes in Carbon disulfide
Cat No.	BWQ8935-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

| Emergency phone number

Emergency phone number	010-58103678

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Flammable liquids	Category 2
Acute Toxicity - Oral	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity -	Category 1
repeated exposure	

| Label elements

Signal word

| Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H361	Suspected of damaging fertility. Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure(kidneys,
	thyroid)

Version: V2.0.0.1 Revision Date: -

| Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

▼ Response	
P321	Specific treatment (see related instructions on the label).
P330	Rinse mouth.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Not applicable.

| Hazard description

Physical and chemical hazards

Highly flammable liquids, its vapor and air mixture can form explosive mixture.

Version: V2.0.0.1 Revision Date: -

Health hazards

Inhaled	Inhalation of the product may produce adverse health effects or irritation of the respiratory tract following discomfort.
Ingestion	(Further see Inhalation).
Skin Contact	MAY BE ABSORBED! Dry skin. Redness. (Further see Inhalation).
Eye	Redness. Pain.

Environmental hazards

Please refer to 12th chapter of SDS.

3 Composition/information on ingredients

Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Chlorobenzene	108-90-7	203-628-5	7.32
1,4-dichlorobenzene	106-46-7	203-400-5	0.07
1,3-dichlorobenzene	541-73-1	208-792-1	0.07
1,2-dichlorobenzene	95-50-1	202-425-9	0.07
1,3,5-trichlorobenzene	108-70-3	203-608-6	0.02
1,3,5-trichlorobenzene	108-70-3	203-608-6	0.02
1,2,3-trichlorobenzene	87-61-6	201-757-1	0.02
1,2,4,5-tetrachlorobenzene	95-94-3	202-466-2	0.004
1,2,3,5-tetrachlorobenzene	634-90-2	211-217-7	0.004
1,2,3,4-tetrachlorobenzene	634-66-2	211-214-0	0.004
Pentachlorobenzene	608-93-5	210-172-0	0.002
Hexachlorobenzene	118-74-1	204-273-9	0.002
Carbon disulphide	75-15-0	200-843-6	92.38

4 First-aid measures

Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the
	doctor in attendance

Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.	
Skin contact First rinse with plenty of water, then remove contaminated clothes and rin again. Refer for medical attention.		
Ingestion Give nothing to drink. Refer for medical attention.		
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.	
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.	

Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- Treat symptomatically.
- Symptoms may be delayed.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
Unsuitable extinguishing media	Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the substance or mixture

- Will form explosive mixtures with air. 2 Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ or vapour concentration. 3 Vapours may travel to source of ignition and flash back. 4
- Liquid and vapour are flammable.
- 5 May emit poisonous fumes on fire.
- 6 Development of hazardous combustion gases or vapor possible in the event of fire.
- 7 May expansion or decompose explosively when heated or involved in fire.

Special protective equipment and precautions for fire-fighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

- Avoid breathing vapours and contacting with skin and eye.
- 2 Beware of vapours accumulating to form explosive concentrations.
- 3 Vapours can accumulate in low areas.

4	Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
5	Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
6	Do not touch or walk through spilled material.
7	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
8	Use personal protective equipment, do not breathe gas/mist/vapour/spray.
9	Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
10	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

- It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
- 2 In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
- In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
- 4 Collect absorbent material using a clean, non-sparking tool.
- 5 Cover with anti-solvent foam to reduce evaporation.
- 6 Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
- 7 Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
- 8 Do not touch or cross spills.
- 9 It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-virus suits.
- 10 Spray water disperses the vapor and dilutes the liquid spill.
- 11 Do not touch broken containers and spills before putting on appropriate protective clothing.
- 12 Cut off the source of the leak as much as possible.
- 13 Keep leaks in a ventilated place.
- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 15 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
- 16 Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
- 17 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7 Handling and storage

Precautions for safe handling

- 1 Avoid inhalation of vapors.
- 2 Use only non-sparking tools.
- 3 To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
- 4 Use explosion proof equipment.
- 5 Handling is performed in a well ventilated place.

6	Wear suitable protective equipment.
7	Avoid contact with skin and eyes.
8	Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

•	
1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.

8 Exposure controls/personal protection

| Control parameters

◆ Occupational exposure limit values

Component	Country/Region	Limit value	- Eight hours	Limit value - Short term	
		ppm	mg/m³	ppm	mg/m³
Chlorobenzene	Japan - JSOH(2024–202 5)	10	46	-	-
	Permissible exposure standards for workers in the workplace	75	345	112.5	431.25
	Australia	10	46	-	-
	Canada - Ontario	10	-	-	-
	European Union	5	23	15	70
	New Zealand	10	46	-	-
1,4-dichlorobenzene	Japan - JSOH(2024–202 5)	10	60	-	-
	Permissible exposure standards for workers in the workplace	75	450	112.5	562.5
	Australia	25	150	50	300
	Canada - Ontario	10	-	-	-
	European Union	2	12	10	60
	New Zealand	2	12	10	60
1,3-dichlorobenzene	Austria	3	20	12	80
	Germany (AGS)	2	12	4	24
	Germany (DFG)	2	12	4	24
	Hungary	-	12	-	24
	Latvia	-	20	-	-
	Switzerland	2	12	4	24
1,2-dichlorobenzene	Japan - JSOH(2024–202	25	150	-	-

	5)				
	Permissible exposure standards for workers in the workplace	-	-	-	-
	Australia	25	150	50	301
	Canada - Ontario	25	-	50	-
	European Union	20	122	50	306
	New Zealand	10	61	20	122
1,3,5-trichlorobenzene	Denmark	5	37	10	74
	Finland	5	38	10	75
	Germany (DFG)	0.5	0.38	1	0.76
	Poland	-	15	-	30
1,3,5-trichlorobenzene	Denmark	5	37	10	74
	Finland	5	38	10	75
	Germany (DFG)	0.5	0.38	1	0.76
	Poland	-	15	-	30
1,2,3-trichlorobenzene	Canada - Ontario	-	-	5	-
	Denmark	5	37	10	76
	Finland	5	38	10	75
	Germany (DFG)	0.5	0.38	1	0.76
	Poland	-	15	-	30
Hexachlorobenzene	Canada - Ontario	-	0.002	-	-
	USA - ACGIH	-	0.002	-	-
	Belgium	-	0.002	-	-
	Canada - Québec	-	0.025	-	-
	Denmark	-	0.025	-	0.05
	Finland	-	0.002	-	-
Carbon disulphide	Japan - JSOH(2024–202 5)	1	3.13	-	-
	Permissible exposure standards for workers in the workplace	10	31	15	46.5
	Australia	10	31	-	-
	Canada - Ontario	1	-	-	-
	European Union	5	15	-	-
	New Zealand	1	3	-	-

| Engineering controls

Version: V2.0.0.1 Revision Date: -

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

| Personal protection equipment

General requirement	
Eye protection	Must wear appropriate safety goggles.
Hand protection	Must wear anti static chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

9 Physical and chemical properties and safety characteristics

| Physical and chemical properties

Appearance (physical state,	colorless liquid
color, etc.)	
Odor	No information available
Odor threshold	No information available
рН	No information available
Melting point/freezing point(°C)	-111 (Carbon disulphide)
Initial boiling point and boiling	46 (Carbon disulphide)
range(°C)	
Flash point(Closed cup,°C)	-30 (Carbon disulphide)
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit: 50 (Carbon disulphide); Lower limit: 1 (Carbon disulphide)
Vapor pressure	48kPa (25°C,Carbon disulphide)
Vapor density(Air = 1)	2.63 (Carbon disulphide)
Relative density(Water=1)	1.26 (Carbon disulphide)
Solubility	2.9g/L (20 °C,Carbon disulphide)
n-octanol/water partition	1.84 (Carbon disulphide)
coefficient	
Auto-ignition temperature(°C)	90 (Carbon disulphide)
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available

10 Stability and reactivity

Stability and reactivity

otability and reactivity		
Reactivity	Contact with incompatible substances can cause decomposition or other	
	chemical reactions.	
Chemical stability	Stable under proper operation and storage conditions.	

Possibility of hazardous	Reactions with metals form metal organic coumpounds. May catch fire
reactions	spontaneously in the air.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Metal, oxidantss and alkali. Nitrate and nitrite, halogens oxyacid salts, potassium
	permanganate, persulfate, halogen and strong oxidants.
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products
products	should not be produced.

11 Toxicological information

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
1,3,5-trichlorobenzene	800mg/kg(Rat)	No information available	No information available
Hexachlorobenzene	10000mg/kg(Rat)	10000mg/kg(Rat)	No information available
1,4-dichlorobenzene	500~5000mg/kg(Rat)	> 2000mg/kg(Rabbit)	No information available
1,2-dichlorobenzene	500mg/kg(Rat)	> 10000mg/kg(Rabbit)	No information available
Pentachlorobenzene	1080mg/kg(Rat)	> 2500mg/kg(Rat)	No information available
1,2,3,5-tetrachlorobenzen e	1727mg/kg(Rat)	No information available	No information available
1,2,3,4-tetrachlorobenzen e	1167mg/kg(Rat)	No information available	No information available
1,2,4,5-tetrachlorobenzen e	1500mg/kg(Rat)	No information available	No information available
1,3,5-trichlorobenzene	800mg/kg(Rat)	No information available	No information available
1,2,3-trichlorobenzene	1830mg/kg(Rat)	No information available	No information available
Chlorobenzene	1110mg/kg(Rat)	No information available	No information available
Carbon disulphide	1200mg/kg(Rat)	No information available	No information available

Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Chlorobenzene	Not Listed	Not Listed	Not Listed
1,4-dichlorobenzene	Category 2B	Category R	Not Listed
1,3-dichlorobenzene	Category 3	Not Listed	Not Listed
1,2-dichlorobenzene	Category 3	Not Listed	Not Listed
1,3,5-trichlorobenzene	Not Listed	Not Listed	Not Listed
1,3,5-trichlorobenzene	Not Listed	Not Listed	Not Listed
1,2,3-trichlorobenzene	Not Listed	Not Listed	Not Listed
1,2,4,5-tetrachlorobenzen e	Not Listed	Not Listed	Not Listed
1,2,3,5-tetrachlorobenzen e	Not Listed	Not Listed	Not Listed
1,2,3,4-tetrachlorobenzen e	Not Listed	Not Listed	Not Listed
Pentachlorobenzene	Not Listed	Not Listed	Not Listed

Hexachlorobenzene	Category 2B	Category R	Not Listed
Carbon disulphide	Not Listed	Not Listed	Not Listed

Others

12 Mix Chlorobenzenes in Carbon disulfide	
Skin corrosion/irritation	Causes skin irritation(Category 2)
Serious eye damage/irritation	Causes serious eye irritation(Category 2)
Skin sensitization	Based on available data, the classification criteria are not met
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child(Category 2)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure(kidneys, thyroid)(Category 1)
Aspiration hazard	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

Ecological information

Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
1,3,5-trichlorobenzene	LC ₅₀ : 3.2mg/L (96h)(Fish)	EC ₅₀ : 2.9mg/L	ErC ₅₀ : >4.8mg/L
		(48h)(Crustaceans)	(72h)(Algae)
Hexachlorobenzene	LC ₅₀ : 7.6mg/L (96h)(Fish)	No information available	No information available
1,4-dichlorobenzene	LC ₅₀ : 2.2mg/L (96h)(Fish)	EC ₅₀ : 2.5mg/L (48h)(Crustaceans)	ErC ₅₀ : 5.4mg/L (72h)(Algae)
1,3-dichlorobenzene	LC ₅₀ : 7.8mg/L (96h)(Fish)	EC ₅₀ : 2.5mg/L (48h)(Crustaceans)	ErC ₅₀ : 126mg/L (96h)(Algae)
1,2-dichlorobenzene	LC ₅₀ : 6.66mg/L (96h)(Fish)	EC ₅₀ : 0.7mg/L (48h)(Crustaceans)	ErC ₅₀ : 71.1mg/L (96h)(Algae)
Pentachlorobenzene	LC ₅₀ : 0.248mg/L (96h)(Fish)	EC ₅₀ : 0.01mg/L (48h)(Crustaceans)	ErC ₅₀ : 6.7mg/L (96h)(Algae)
1,2,3,5-tetrachlorobenzen e	LC ₅₀ : 5.05mg/L (96h)(Fish)	No information available	ErC ₅₀ : 17.4mg/L (96h)(Algae)
1,2,3,4-tetrachlorobenzen e	LC ₅₀ : 1.1 mg/L (96h)(Fish)	EC ₅₀ : 0.13mg/L (48h)(Crustaceans)	No information available
1,2,4,5-tetrachlorobenzen e	LC ₅₀ : 2.12mg/L (96h)(Fish)	No information available	ErC ₅₀ : 49.8mg/L (96h)(Algae)
1,3,5-trichlorobenzene	LC ₅₀ : 3.2mg/L (96h)(Fish)	EC ₅₀ : 2.9mg/L (48h)(Crustaceans)	ErC ₅₀ : >4.8mg/L (72h)(Algae)
1,2,3-trichlorobenzene	LC ₅₀ : 3.2mg/L (96h)(Fish)	EC ₅₀ : 0.46mg/L (48h)(Crustaceans)	ErC ₅₀ : 0.9mg/L (96h)(Algae)
Chlorobenzene	LC ₅₀ : 6.6mg/L (96h)(Fish)	EC ₅₀ : 5.29mg/L (48h)(Crustaceans)	ErC ₅₀ : 202mg/L (96h)(Algae)
Carbon disulphide	LC ₅₀ : 3mg/L (96h)(Fish)	No information available	ErC ₅₀ : 21mg/L (96h)(Algae)

| Chronic aquatic toxicity

| Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
1,3-dichlorobenzene	High(Half-life = 360 days)	Low(Half-life = 37.13 days)
1,2-dichlorobenzene	High(Half-life = 360 days)	Medium(Half-life = 63.67 days)
1,3,5-trichlorobenzene	High	High
1,3,5-trichlorobenzene	High	High
1,2,3-trichlorobenzene	High	High
1,2,4,5-tetrachlorobenzen e	High(Half-life = 360 days)	High(Half-life = 317.96 days)
1,2,3,5-tetrachlorobenzen e	High	High
1,2,3,4-tetrachlorobenzen e	High	High
Pentachlorobenzene	High(Half-life = 690 days)	High(Half-life = 453.21 days)
Hexachlorobenzene	High(Half-life = 4178 days)	High(Half-life = 1563.75 days)

| Bioaccumulative potential

Component	Bioaccumulative potential	Comments
1,3-dichlorobenzene	High	BCF=6918
1,2-dichlorobenzene	Low	BCF=260
1,3,5-trichlorobenzene	Medium	Log Kow=4.19
1,3,5-trichlorobenzene	Medium	Log Kow=4.19
1,2,3-trichlorobenzene	Medium	Log Kow=4.05
1,2,4,5-tetrachlorobenzen e	High	BCF=4830
1,2,3,5-tetrachlorobenzen e	High	Log Kow=4.56
1,2,3,4-tetrachlorobenzen e	Medium	BCF=1710

Pentachlorobenzene	High	BCF=6840
Hexachlorobenzene	High	BCF=575440

| Mobility in soil

Component	log Koc	Remark
Chlorobenzene	2.369	MCI method
1,3-dichlorobenzene	2.5	
1,2-dichlorobenzene	2.65	20 ℃
1,3,5-trichlorobenzene	2.847	
1,3,5-trichlorobenzene	2.847	
1,2,3-trichlorobenzene	2.87	
1,2,4,5-tetrachlorobenzen e	3.074	
1,2,3,5-tetrachlorobenzen e	3.074	
1,2,3,4-tetrachlorobenzen e	3.083	
Pentachlorobenzene	3.301	
Hexachlorobenzene	3.529	
Carbon disulphide	1.53	20 ℃

13 Disposal considerations

| Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

Transport information

Label and Mark

Transporting Label



IMDG-CODE

UN number	1131
UN proper shipping name	CARBON DISULPHIDE
Transport hazard class	3
Transport subsidiary hazard	6.1
class	
Packing group	I

12 Mix Chlorobenzenes in Carbon o	disulfide Version: V2.0.0.1 Revision Date: -
Marine pollutant (Yes or no)	No
IATA-DGR	
UN number	1131
UN proper shipping name	CARBON DISULPHIDE
Transport hazard class	3
Transport subsidiary hazard class	6.1
Packing group	I
UN-ADR	
UN number	1131
UN proper shipping name	CARBON DISULPHIDE
Transport hazard class	3
Transport subsidiary hazard class	6.1
Packing group	I
Transport in bulk according t	o IMO instruments
◆ Transport in bulk according	to Annex II of MARPOL and the IBC code
	Not Available
◆Transport in bulk in accorda	nce with MARPOL Annex V and the IMSBC Code
	Not Available
Transport in bulk in accorda	nce with the IGC Code
	Not Available
Others	
Precautions for transport	Transit should be anti-exposure, rain, high temperature. Strictly prohibited shipping or transportation with acids, alkalis, oxidants, food and food additives etc. Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport

15 Regulatory information

International chemical inventory

Component	Α	В	С	D	E	F	G	Н	I	J	K	L	M
Chlorobenzene	√	√	√	√	√	√	√	√	√	√	√	√	√

transporting requirements.

vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport,

should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant

1,4-dichlorobenzene	√	√	$\sqrt{}$	√	√	√	√	√	√		√	√	√
1,3-dichlorobenzene	√	√	√	√	√	√	√	√	√	×	√	√	√
1,2-dichlorobenzene	√	V	√	√	√	√	√	√	√	√	√	√	√
1,3,5-trichlorobenzene	√	V	√	√	√	√	×	√	√	×	√	√	√
1,3,5-trichlorobenzene	√	V	√	√	√	√	×	√	√	×	√	√	√
1,2,3-trichlorobenzene	√	1	V	√	√	√	V	√	√	√	×	√	√
1,2,4,5-tetrachlorobenzen e	√	V	√	√	×	×	×	×	√	×	√	V	√
1,2,3,5-tetrachlorobenzen e	1	1	1	×	×	×	×	1	1	×	×	1	1
1,2,3,4-tetrachlorobenzen e	1	√	V	√	×	V	×	V	√	×	×	√	V
Pentachlorobenzene	√	√	√	√	×	×	×	√	√	×	√	√	√
Hexachlorobenzene	√	V	√	√	×	√	×	√	√	√	√	√	√
Carbon disulphide	√	1	V	√	1	√	V	√	1	√	V	V	√

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZloC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	Α	В	С
Chlorobenzene	×	×	×
1,4-dichlorobenzene	×	×	×
1,3-dichlorobenzene	×	×	×
1,2-dichlorobenzene	×	×	×
1,3,5-trichlorobenzene	×	×	×
1,3,5-trichlorobenzene	×	×	×
1,2,3-trichlorobenzene	×	×	×
1,2,4,5-tetrachlorobenzen e	×	×	×
1,2,3,5-tetrachlorobenzen e	×	×	×
1,2,3,4-tetrachlorobenzen e	×	×	×
Pentachlorobenzene	×	V	×
Hexachlorobenzene	×	V	V
Carbon disulphide	×	×	×

(B) Stockholm Convention on Persistent Organic Pollutants (POPs)

The Montreal Protocol on Substances that Deplete the Ozone Layer

- Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in [C] international trade

US chemical inventory

(A)

Component	Α	В	С	D	E	F	G	Н
Chlorobenzene	$\sqrt{}$	×	√	√	√	√	√	×
1,4-dichlorobenzene	V	×	√	√	√	√	√	√
1,3-dichlorobenzene	×	×	√	√	√	√	√	×
1,2-dichlorobenzene	×	×	√	√	√	√	√	×
1,3,5-trichlorobenzene	×	×	×	×	×	×	×	×
1,3,5-trichlorobenzene	×	×	×	×	×	×	×	×
1,2,3-trichlorobenzene	×	×	×	√	×	×	√	×
1,2,4,5-tetrachlorobenze ne	×	×	V	V	√	V	V	×
1,2,3,5-tetrachlorobenze ne	×	×	×	×	×	×	×	×
1,2,3,4-tetrachlorobenze ne	×	×	×	×	×	×	×	×
Pentachlorobenzene	×	×	√	√	√	√	√	×
Hexachlorobenzene	V	×	√	√	√	√	√	√
Carbon disulphide	√	√	√	√	√	√	√	√

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- US New York City Right-to-Know Hazardous Substance List [G]
- US California Proposition 65 List [H]

Note:

- Indicates that the substance included in the regulations.
- No data or not included in the regulations.

Other information

Information on revision

Creation Date	2025/10/13
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/. [3]
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/. [6]
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.

[8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

| Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG- CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC_X	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
P_{OW}	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

Version: V2.0.0.1 Revision Date: -

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.