### **Safety Data Sheet**

## 11 Mix VOCs in methanol

Version: V2.0.0.1

Report No.: BWQ9603-2016-MSDS-US

Creation Date: 2025/11/06

Revision Date: -



#### \*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1 Identification

### | Product identifier

Product Name	11 Mix VOCs in methanol
Cat No.	BWQ9603-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

### Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

### Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

### | Emergency phone number

Г	mla a ma muuma la a m	040 50400070
Emergency	phone number	010-58103678

2 Hazard(s) identification

### Hazard classification according to 29 CFR 1910.1200

Acute Toxicity - Oral	Category 3
Acute Toxicity - Dermal	Category 3
Acute Toxicity - Inhalation	Category 3
Specific target organ toxicity -	Category 1
single exposure	

#### Label elements

**Hazard pictograms** 





Composition/information on ingredients

Signal word	Danger
Hazard statements	
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs
Precautionary statements	
<ul><li>Prevention</li></ul>	
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or with adequate ventilation.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
◆ Response	
P321	Specific treatment (see related instructions on the label).
P330	Rinse mouth.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P361+P364	Take off immediately all contaminated clothing and wash it before reuse.
◆ Storage	
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
◆ Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	
O THOSE HOME OF	Not applicable.
Hazard description	
<ul> <li>Physical and chemical haz</li> </ul>	ards
	No information available
<ul><li>Health hazards</li></ul>	
Inhaled	Cough. Dizziness. Headache. Nausea. Weakness. Visual disturbance.
Ingestion	Abdominal pain. Shortness of breath. Vomiting. Convulsions. Unconsciousness (Further see Inhalation).
Skin Contact	MAY BE ABSORBED! Dry skin. Redness.
Eye	Redness. Pain.
Environmental hazards	
LIMIOIIIIGIIIAI IIAZAIUS	

2 / 15

Version: V2.0.0.1 Revision Date: -

#### Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Methanol	67-56-1	200-659-6	99.899
Dichloromethane	75-09-2	200-838-9	0.0240
Benzene	71-43-2	200-753-7	0.00574444444
Toluene	108-88-3	203-625-9	0.00574444444
1,2-dichloroethane	107-06-2	203-458-1	0.0253
Ethylbenzene	100-41-4	202-849-4	0.00574444444
p-xylene	106-42-3	203-396-5	0.00574444444
m-xylene	108-38-3	203-576-3	0.00574444444
Cumene	98-82-8	202-704-5	0.00574444444
o-xylene	95-47-6	202-422-2	0.00574444444
Chlorobenzene	108-90-7	203-628-5	0.00574444444
Styrene	100-42-5	202-851-5	0.00574444444

## 4 First-aid measures

### Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
Skin contact	Remove contaminated clothes. Rinse skin with plenty of water or shower. Refer for medical attention.
Ingestion	Induce vomiting (ONLY IN CONSCIOUS PERSONS!). Refer for medical attention.
Inhalation	Fresh air, rest. Refer for medical attention.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

### Most important symptoms/effects, acute and delayed

1 Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

### Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

# 5 Fire-fighting measures

### | Extinguishing media

Suitable extinguishing media	Use extinguishing media suitable for surrounding area.
Unsuitable extinguishing media	There is no restriction on the type of extinguisher which may be used.

### Specific hazards arising from the substance or mixture

- 1 Development of hazardous combustion gases or vapor possible in the event of fire.
- 2 May expansion or decompose explosively when heated or involved in fire.

### Special protective equipment and precautions for fire-fighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

## 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- 1 Use personal protective equipment, do not breathe gas/mist/vapour/spray.
- Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
- 3 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

### **Environmental precautions**

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

### Methods and materials for containment and cleaning up

- 1 Cut off the source of the leak as much as possible.
- 2 Keep leaks in a ventilated place.
- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 4 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
- Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.

## 7 Handling and storage

### Precautions for safe handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.

### Conditions for safe storage, including any incompatibilities

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

## 8 Exposure controls/personal protection

### **Control parameters**

## ◆ Occupational exposure limit values

Component	Country/Region	Limit value -	Eight hours	Limit value - Short term	
		ppm	mg/m³	ppm	mg/m³
Methanol	Japan - JSOH(2024–202 5)	200	260	-	-
	Permissible exposure standards for workers in the workplace	200	262	250	327.5
	Australia	200	262	250	328
	Canada - Ontario	200	-	250	-
	European Union	200	260	-	-
	New Zealand	200	262	250	328
Dichloromethane	Japan - JSOH(2024–202 5)	50	173	-	-
	Permissible exposure standards for workers in the workplace	50	174	75	217.5
	Australia	50	174	-	-
	Canada - Ontario	50	-	-	-
	European Union	100	353	200	706
	New Zealand	50	174	-	-
Benzene	Japan - JSOH(2024–202 5)	1(individual excess lifetime risk of cancer 10^-3)	-	-	-
	Permissible exposure standards for workers in the workplace	1	3.2	2	6.4
	Australia	1	3.2	-	-
	Canada - Ontario	0.5	-	2.5	-
	European Union	0.2	0.66	-	-
	New Zealand	0.05	0.16	-	-
Toluene	Japan - JSOH(2024–202 5)	50	188	-	-
	Permissible exposure standards for workers in the workplace	50	188	75	235
	Australia	50	191	150	574
	Canada - Ontario	20	-	-	-

	European Union	50	192	100	384
	New Zealand	20	75	100	377
1,2-dichloroethane	Japan - JSOH(2024–202 5)	10	40	-	-
	Permissible exposure standards for workers in the workplace	10	40	15	60
	Australia	10	40	-	-
	Canada - Ontario	10	-	-	-
	European Union	2	8.2	-	-
	New Zealand	5	21	-	-
Ethylbenzene	Japan - JSOH(2024–202 5)	20	87	-	-
	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	Australia	100	434	125	543
	Canada - Ontario	20	-	-	-
	European Union	100	442	200	884
	New Zealand	20	88	40	176
p-xylene	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	Australia	80	350	150	655
	Canada - Ontario	100	-	150	-
	European Union	50	221	100	442
	New Zealand	50	217	-	-
	USA - ACGIH	20	-	-	-
m-xylene	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	Australia	80	350	150	655
	Canada - Ontario	100	-	150	-
	European Union	50	221	100	442
	New Zealand	50	217	-	-
	USA - ACGIH	20	-	-	-
Cumene	Japan - JSOH(2024–202 5)	10	50	-	-

	Permissible exposure standards for workers in the workplace	50	246	75	307.5
	Australia	25	125	75	375
	Canada - Ontario	50	-	-	-
	European Union	10	50	50	250
	New Zealand	25	125	75	375
o-xylene	Permissible exposure standards for workers in the workplace	100	434	125	542.5
	Australia	80	350	150	655
	Canada - Ontario	100	-	150	-
	European Union	50	221	100	442
	New Zealand	50	217	-	-
	USA - ACGIH	20	-	-	-
Chlorobenzene	Japan - JSOH(2024–202 5)	10	46	-	-
	Permissible exposure standards for workers in the workplace	75	345	112.5	431.25
	Australia	10	46	-	-
	Canada - Ontario	10	-	-	-
	European Union	5	23	15	70
	New Zealand	10	46	-	-
Styrene	Japan - JSOH(2024–202 5)	10	42.6	-	-
	Permissible exposure standards for workers in the workplace	50	213	75	266.25
	Australia	50	213	100	426
	Canada - Ontario	35	-	100	-
	New Zealand	20	85	40	170
	USA - ACGIH	10	-	20	_

## | Engineering controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

## | Personal protection equipment

General requirement		
Eye protection	Must wear appropriate safety goggles.	
Hand protection	Must wear appropriate chemical protective gloves.	
Respiratory protection	Must wear appropriate personal dust proof gas mask.	
Skin and body protection	Must wear appropriate chemical protective clothing and chemical resistant shoes.	

Version: V2.0.0.1 Revision Date: -

# 9 Physical and chemical properties and safety characteristics

## | Physical and chemical properties

Appearance (physical state,	Clear, colorless liquid
color, etc.)	
Odor	No information available
Odor threshold	No information available
рН	No information available
Melting point/freezing point(°C)	No information available
Initial boiling point and boiling	>35
range(°C)	
Flash point(Closed cup,°C)	No information available
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit: No information available; Lower limit: No information available
Vapor pressure	No information available
Vapor density(Air = 1)	No information available
Relative density(Water=1)	No information available
Solubility	No information available
n-octanol/water partition coefficient	No information available
Auto-ignition temperature(°C)	No information available
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available

# 10 Stability and reactivity

## | Stability and reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions	In contact with oxidants causes severe reactions, and may cause a fire or explosion. Reactions with metals form metal organic coumpounds. In contact with halides may cause an active reaction.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Oxidants, alkali metals, alkaline earth metals and aluminum. Metal, oxidantss and

	alkali. Halides, oxidants and halogen.
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products
products	should not be produced.

# 11 Toxicological information

## Acute toxicity

Component	LD <sub>50</sub> (oral)	LD <sub>50</sub> (dermal)	LC <sub>50</sub> (inhalation,4h)
Chlorobenzene	1110mg/kg(Rat)	No information available	No information available
Dichloromethane	1600mg/kg(Rat)	No information available	No information available
Benzene	930mg/kg(Rat)	> 8260mg/kg(Rabbit)	No information available
Toluene	636mg/kg(Rat)	12200mg/kg(Rabbit)	49mg/L(Rat)
Cumene	1400mg/kg(Rat)	10600mg/kg(Rabbit)	No information available
Styrene	2650mg/kg(Rat)	No information available	12mg/L(Rat)
1,2-dichloroethane	670mg/kg(Rat)	2800mg/kg(Rabbit)	No information available
Ethylbenzene	3500mg/kg(Rat)	15400mg/kg(Rabbit)	No information available
Methanol	5628mg/kg(Rat)	15800mg/kg(Rabbit)	83.867mg/L(Rat)
m-xylene	5000mg/kg(Rat)	12200mg/kg(Rabbit)	No information available
p-xylene	5000mg/kg(Rat)	No information available	19.758mg/L(Rat)

## | Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Methanol	Not Listed	Not Listed	Not Listed
Dichloromethane	Category 2A	Category R	Listed
Benzene	Category 1	Category K	Listed
Toluene	Category 3	Not Listed	Not Listed
1,2-dichloroethane	Category 2B	Category R	Not Listed
Ethylbenzene	Category 2B	Not Listed	Not Listed
p-xylene	Not Listed	Not Listed	Not Listed
m-xylene	Not Listed	Not Listed	Not Listed
Cumene	Category 2B	Category R	Not Listed
o-xylene	Not Listed	Not Listed	Not Listed
Chlorobenzene	Not Listed	Not Listed	Not Listed
Styrene	Category 2A	Category R	Not Listed

## Others

11 Mix VOCs in methanol		
Skin corrosion/irritation	Based on available data, the classification criteria are not met	
Serious eye damage/irritation	Based on available data, the classification criteria are not met	
Skin sensitization	Based on available data, the classification criteria are not met	

Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Causes damage to organs(Category 1)
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

# 12 Ecological information

## | Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Chlorobenzene	LC <sub>50</sub> : 6.6mg/L (96h)(Fish)	EC <sub>50</sub> : 5.29mg/L	ErC <sub>50</sub> : 202mg/L
		(48h)(Crustaceans)	(96h)(Algae)
Dichloromethane	LC <sub>50</sub> :193mg/L (96h)(Fish)	EC <sub>50</sub> : 1470mg/L	No information available
		(48h)(Crustaceans)	
Benzene	LC <sub>50</sub> : 21.6mg/L	EC <sub>50</sub> : 10.9mg/L	ErC <sub>50</sub> : 1600mg/L
	(96h)(Fish)	(48h)(Crustaceans)	(96h)(Algae)
Toluene	LC <sub>50</sub> : 25mg/L (96h)(Fish)	EC <sub>50</sub> : 4.1mg/L	ErC <sub>50</sub> : 29mg/L
		(48h)(Crustaceans)	(72h)(Algae)
Cumene	LC <sub>50</sub> : 4.8mg/L (96h)(Fish)	EC <sub>50</sub> : 10.6mg/L	No information available
		(48h)(Crustaceans)	
Styrene	LC <sub>50</sub> : 4.02mg/L	EC <sub>50</sub> : 4.7mg/L	ErC <sub>50</sub> : 0.72mg/L
	(96h)(Fish)	(48h)(Crustaceans)	(96h)(Algae)
1,2-dichloroethane	LC <sub>50</sub> :136mg/L (96h)(Fish)	EC <sub>50</sub> : 99mg/L	ErC <sub>50</sub> : 230mg/L
		(48h)(Crustaceans)	(72h)(Algae)
o-xylene	LC <sub>50</sub> : 16.1mg/L	EC <sub>50</sub> : 1.1mg/L	ErC <sub>50</sub> : 0.80mg/L
	(96h)(Fish)	(48h)(Crustaceans)	(72h)(Algae)
Ethylbenzene	LC <sub>50</sub> : 4.2mg/L (96h)(Fish)	EC <sub>50</sub> : 4.75mg/L	ErC <sub>50</sub> : 3.6mg/L
		(48h)(Crustaceans)	(96h)(Algae)
Methanol	LC <sub>50</sub> : 24000mg/L	EC <sub>50</sub> : 24500mg/L	No information available
	(96h)(Fish)	(48h)(Crustaceans)	
m-xylene	LC <sub>50</sub> : 10.6mg/L	EC <sub>50</sub> : 2.4mg/L	ErC <sub>50</sub> : 8.9mg/L
	(96h)(Fish)	(48h)(Crustaceans)	(72h)(Algae)
p-xylene	LC <sub>50</sub> : 5.5mg/L (96h)(Fish)	EC <sub>50</sub> : 6.9mg/L	ErC <sub>50</sub> : 9.6mg/L
		(48h)(Crustaceans)	(72h)(Algae)

## | Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Chlorobenzene	No information available	NOEC : 0.72mg/L(Crustaceans)	No information available
Toluene	No information available	NOEC : 1.2mg/L(Crustaceans)	NOEC: 9.1mg/L(Algae)
1,2-dichloroethane	NOEC: 41mg/L(Fish)	NOEC : 1.0mg/L(Crustaceans)	NOEC : 55mg/L(Algae)
o-xylene	No information available	NOEC : 0.63mg/L(Crustaceans)	NOEC: 0.73mg/L(Algae)
m-xylene	No information available	NOEC : 0.41mg/L(Crustaceans)	NOEC: 5.3mg/L(Algae)

p-xylene No information available NOEC : NOEC : 4.4mg/L(Algae)
1.3mg/L(Crustaceans)

Version: V2.0.0.1 Revision Date: -

## | Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Methanol	Low	Low
p-xylene	High(Half-life = 360 days)	Low(Half-life = 1.75 days)
m-xylene	High(Half-life = 360 days)	Low(Half-life = 1.08 days)
o-xylene	High(Half-life = 360 days)	Low(Half-life = 1.83 days)

## | Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Methanol	Low	BCF=10
p-xylene	Low	BCF=2.2
m-xylene	Low	BCF=1.37
o-xylene	Low	BCF=219

## Mobility in soil

Component	log Koc	Remark
Methanol	0.000	
Dichloromethane	1.67	20 ℃
Benzene	2.13	20 ℃
Toluene	2.31	20 ℃
Ethylbenzene	3.12	20 ℃
p-xylene	2.73	20 ℃
m-xylene	2.73	20 ℃
Cumene	2.95	20 ℃
o-xylene	2.73	20 ℃
Chlorobenzene	2.369	MCI method
Styrene	2.55	

## 13 Disposal considerations

## Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and			
	regulation. Recommend the use of incineration disposal.			
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot			
	and ignition source of fire. Return to supplier for recycling if possible.			
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.			

# 14 Transport information

### Label and Mark

Transporting Label | Not applicable

#### IMDG-CODE

IMDG-CODE NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### IATA-DGR

IATA-DGR NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### UN-ADR

UN-ADR NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

### Others

**Precautions for transport** 

Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

Version: V2.0.0.1 Revision Date: -

## 15 Regulatory information

### International chemical inventory

Component	Α	В	С	D	E	F	G	н	I	J	K	L	M
Methanol	√	<b>√</b>	√	√	√	√	√	√	√	√	√	√	<b>V</b>
Dichloromethane	√	<b>√</b>	<b>√</b>	√	<b>√</b>	√	<b>√</b>						
Benzene	√	<b>√</b>	√	<b>√</b>	<b>√</b>	<b>√</b>							
Toluene	√	<b>√</b>	<b>√</b>	√	<b>√</b>	√	<b>√</b>						
1,2-dichloroethane	√	<b>√</b>	<b>√</b>	√	<b>√</b>	√	<b>√</b>						
Ethylbenzene	√	<b>√</b>	<b>√</b>	√	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	√	<b>√</b>	√	1
p-xylene	√	<b>√</b>	1										
m-xylene	√	<b>√</b>	√	<b>√</b>	<b>√</b>	<b>V</b>							
Cumene	√	<b>√</b>	√										
o-xylene	√	<b>√</b>	1										
Chlorobenzene	<b>√</b>	1	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	1	<b>√</b>	<b>√</b>	<b>√</b>	1
Styrene	√	1	<b>√</b>	<b>√</b>	1	1	<b>√</b>	1	<b>√</b>	<b>√</b>	1	<b>√</b>	1

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)

- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZloC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- **[G]** Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

### List of Chemical Substances under International Conventions

Component	A	В	С
Methanol	×	×	×
Dichloromethane	×	×	×
Benzene	×	×	×
Toluene	×	×	×
1,2-dichloroethane	×	×	V
Ethylbenzene	×	×	×
p-xylene	×	×	×
m-xylene	×	×	×
Cumene	×	×	×
o-xylene	×	×	×
Chlorobenzene	×	×	×
Styrene	×	×	×

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

### US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Methanol	√	×	√	√	√	√	√	√
Dichloromethane	√	×	√	<b>√</b>	√	√	√	√
Benzene	√	×	<b>√</b>	<b>√</b>	<b>√</b>	√	√	√
Toluene	√	×	√	√	√	√	√	√
1,2-dichloroethane	<b>√</b>	×	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>
Ethylbenzene	√	×	√	<b>√</b>	√	√	√	<b>√</b>
p-xylene	√	×	√	<b>√</b>	√	√	√	×
m-xylene	√	×	√	<b>√</b>	√	√	√	×
Cumene	√	×	√	<b>√</b>	√	√	√	<b>√</b>
o-xylene	<b>√</b>	×	<b>√</b>	<b>V</b>	<b>√</b>	<b>√</b>	<b>√</b>	×
Chlorobenzene	√ √	×	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

#### Note:

- " $\sqrt{\phantom{a}}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

## 16 Other information

### Information on revision

Creation Date	2025/11/06
Revision Date	-
Reason for revision	-

#### Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- $[7] \qquad \text{U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.} \\$
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

#### Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-	International Maritime Dangerous Goods CODE
I C-IVVA	Time Weighted Average	CODE	international Mantine Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC <sub>50</sub>	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD <sub>50</sub>	Lethal Dose 50%	NTP	National Toxicology Program
EC <sub>50</sub>	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
$EC_X$	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
Pow	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

### Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume

responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.