Safety Data Sheet

Isobutanol in Isopropyl Alcohol/Carbon disulfide

Version: V2.0.0.1

Report No.: BWQ9681-2016-MSDS-US

Creation Date: 2025/10/13

Revision Date: -

*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)



1 Identification

| Product identifier

<u> </u>		
Product Name	Isobutanol in Isopropyl Alcohol/Carbon disulfide	
Cat No.	BWQ9681-2016	
CAS No.	Not applicable	
EC No.	Not applicable	
Molecular Formula	Not applicable	

Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

| Emergency phone number

Emergency phone number	010-58103678

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Flammable liquids	Category 2
Acute Toxicity - Oral	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity -	Category 1
repeated exposure	

Label elements

| Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H361	Suspected of damaging fertility. Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

Version: V2.0.0.1 Revision Date: -

| Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

◆ Response

P321	Specific treatment (see related instructions on the label).
P330	Rinse mouth.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	Small fire: dry chemical, CO ₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Not applicable.

| Hazard description

Physical and chemical hazards

Highly flammable liquids, its vapor and air mixture can form explosive mixture.

Version: V2.0.0.1 Revision Date: -

Health hazards

Inhaled	Inhalation of the product may produce adverse health effects or irritation of the respiratory tract following discomfort.	
Ingestion	(Further see Inhalation).	
Skin Contact	MAY BE ABSORBED! Dry skin. Redness. (Further see Inhalation).	
Eye	Redness. Pain.	

Environmental hazards

Please refer to 12th chapter of SDS.

3 Composition/information on ingredients

Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
2-methylpropan-1-ol	78-83-1	201-148-0	0.079
Propan-2-ol	67-63-0	200-661-7	1.998
Carbon disulphide	75-15-0	200-843-6	97.923

4 First-aid measures

Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
	doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
Skin contact	First rinse with plenty of water, then remove contaminated clothes and rinse again. Refer for medical attention.
Ingestion	Give nothing to drink. Refer for medical attention.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Version: V2.0.0.1 Revision Date: -Indication of any immediate medical attention and special treatment needed Treat symptomatically. 2 Symptoms may be delayed. Fire-fighting measures Extinguishing media Suitable extinguishing media Small fire: dry chemical, CO₂ or alcohol-resistant foam; Large fire: alcohol-resistant foam; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Unsuitable extinguishing media Use of water spray when fighting fire may be inefficient. Specific hazards arising from the substance or mixture 1 Will form explosive mixtures with air. 2 Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ or vapour concentration. 3 Vapours may travel to source of ignition and flash back. 4 Liquid and vapour are flammable. 5 May emit poisonous fumes on fire. 6 Development of hazardous combustion gases or vapor possible in the event of fire. 7 May expansion or decompose explosively when heated or involved in fire. Special protective equipment and precautions for fire-fighters As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear. 2 Fight fire from a safe distance, with adequate cover. 3 Prevent fire extinguishing water from contaminating surface water or the ground water system. Accidental release measures Personal precautions, protective equipment and emergency procedures Avoid breathing vapours and contacting with skin and eye. 2 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. 3 4 Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves. 5 Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch or walk through spilled material. 6

| Environmental precautions

discharges.

7

8 9

10

1	Prevent further leakage or spillage if safe to do so.
2	Discharge into the environment must be avoided.

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static

Use personal protective equipment, do not breathe gas/mist/vapour/spray.

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Methods and materials for containment and cleaning up

1 It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.

Version: V2.0.0.1 Revision Date: -

- 2 In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
- In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
- 4 Collect absorbent material using a clean, non-sparking tool.
- 5 Cover with anti-solvent foam to reduce evaporation.
- 6 Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
- 7 Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
- 8 Do not touch or cross spills.
- 9 It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-virus suits.
- 10 Spray water disperses the vapor and dilutes the liquid spill.
- 11 Do not touch broken containers and spills before putting on appropriate protective clothing.
- 12 Cut off the source of the leak as much as possible.
- 13 Keep leaks in a ventilated place.
- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 15 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
- 16 Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
- 17 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7 Handling and storage

Precautions for safe handling

- 1 Avoid inhalation of vapors.
- 2 Use only non-sparking tools.
- 3 To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
- 4 Use explosion proof equipment.
- 5 Handling is performed in a well ventilated place.
- 6 Wear suitable protective equipment.
- 7 Avoid contact with skin and eyes.
- 8 Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/hot surfaces.

8 Exposure controls/personal protection

| Control parameters

Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m³	ppm	mg/m³
2-methylpropan-1-ol	Japan - JSOH(2024–202 5)	50	150	-	-
	Permissible exposure standards for workers in the workplace	50	152	75	190
	Canada - Ontario	50	-	-	-
	New Zealand	50	152	-	-
	USA - ACGIH	50	-	-	-
	USA - NIOSH	50	150	-	-
Propan-2-ol	Japan - JSOH(2024–202 5)	-	-	-	-
	Permissible exposure standards for workers in the workplace	400	983	500	1228.75
	Australia	400	983	500	1230
	Canada - Ontario	200	-	400	-
	New Zealand	400	983	500	1230
	USA - ACGIH	200	-	400	-
Carbon disulphide	Japan - JSOH(2024–202 5)	1	3.13	-	-
	Permissible exposure standards for workers in the workplace	10	31	15	46.5
	Australia	10	31	-	-
	Canada - Ontario	1	-	-	-
	European Union	5	15	-	-
	New Zealand	1	3	-	-

| Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

| Personal protection equipment

Version: V2.0.0.1 Revision Date: -

General requirement			
Eye protection	Must wear appropriate safety goggles.		
Hand protection	Must wear anti static chemical protective gloves.		
Respiratory protection	Must wear appropriate personal respiratory protective equipment.		
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.		

Version: V2.0.0.1 Revision Date: -

Physical and chemical properties and safety characteristics

| Physical and chemical properties Appearance (physical state, Clear, colorless liquid color, etc.) Odor No information available Odor threshold No information available No information available Hq Melting point/freezing point(°C) -111 (Carbon disulphide) Initial boiling point and boiling 46 (Carbon disulphide) range(°C) Flash point(Closed cup, °C) -30 (Carbon disulphide) **Evaporation rate** No information available **Flammability** No information available Upper/lower explosive Upper limit: 50 (Carbon disulphide); Lower limit: 1 (Carbon disulphide) limits[%(v/v)] Vapor pressure 48kPa (25°C, Carbon disulphide) Vapor density(Air = 1) 2.63 (Carbon disulphide) Relative density(Water=1) 1.26 (Carbon disulphide) Solubility 2.9g/L (20 °C, Carbon disulphide) n-octanol/water partition 1.84 (Carbon disulphide) coefficient Auto-ignition temperature(°C) 90 (Carbon disulphide) No information available Decomposition temperature(°C) Kinematic viscosity No information available

Stability and reactivity

Stability and reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions Conditions to avoid	In contact with oxidants causes severe reactions, and may cause a fire or explosion. May catch fire spontaneously in the air. Incompatible materials, heat, flame and spark.
Incompatible materials	Oxidants, alkali metals, alkaline earth metals and aluminum. Nitrate and nitrite, halogens oxyacid salts, potassium permanganate, persulfate, halogen and strong oxidants.
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products

nroducte	should not be produced
Dioducia	i Silvulu ilvi de divuuceu.

Version: V2.0.0.1 Revision Date: -

11 Toxicological information

| Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Propan-2-ol	5045mg/kg(Rat)	12800mg/kg(Rabbit)	No information available
2-methylpropan-1-ol	2460mg/kg(Rat)	3400mg/kg(Rabbit)	No information available
Carbon disulphide	1200mg/kg(Rat)	No information available	No information available

| Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
2-methylpropan-1-ol	Not Listed	Not Listed	Not Listed
Propan-2-ol	Category 3	Not Listed	Not Listed
Carbon disulphide	Not Listed	Not Listed	Not Listed

Others

Isobutanol in Isopropyl Alcohol/Carbon disulfide				
Skin corrosion/irritation Causes skin irritation(Category 2)				
Serious eye damage/irritation	Causes serious eye irritation(Category 2)			
Skin sensitization Based on available data, the classification criteria are not met				
Respiratory sensitization	Based on available data, the classification criteria are not met			
Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child(Category 2)			
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure(Category 1)			
Aspiration hazard	Based on available data, the classification criteria are not met			
Germ cell mutagenicity	Based on available data, the classification criteria are not met			

12 Ecological information

| Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Propan-2-ol	LC ₅₀ : 9640mg/L	EC ₅₀ : >1000mg/L	ErC ₅₀ : >1000mg/L
	(96h)(Fish)	(48h)(Crustaceans)	(72h)(Algae)
2-methylpropan-1-ol	LC ₅₀ : 1510mg/L	EC ₅₀ : 1200mg/L	No information available
	(96h)(Fish)	(48h)(Crustaceans)	
Carbon disulphide	LC ₅₀ : 3mg/L (96h)(Fish)	No information available	ErC ₅₀ : 21mg/L
			(96h)(Algae)

| Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Propan-2-ol	NOEC: > 100mg/L(Fish)	NOEC: >100mg/L(Crusta	NOEC: 1000mg/L(Algae)
		ceans)	

Persistence and degradability

Persistence and degradability No information available

| Bioaccumulative potential

Bioaccumulative potential No information available

Mobility in soil

Component	log Koc	Remark
Propan-2-ol	0.54	20 ℃
Carbon disulphide	1.53	20 ℃

Version: V2.0.0.1 Revision Date: -

13 Disposal considerations

| Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.	
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.	
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.	

14 Transport information

| Label and Mark

Transporting Label





| IMDG-CODE

UN number	1131			
UN proper shipping name	CARBON DISULPHIDE			
Transport hazard class	3			
Transport subsidiary hazard	6.1			
class				
Packing group	I			
Marine pollutant (Yes or no)	No			

IATA-DGR

UN number	1131
UN proper shipping name	CARBON DISULPHIDE
Transport hazard class	3
Transport subsidiary hazard	6.1
class	
Packing group	I

UN-ADR

UN number	1131
	l .

UN proper shipping name	CARBON DISULPHIDE	
Transport hazard class	3	
Transport subsidiary hazard	6.1	
class		
Packing group	I	

Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

Others

Precautions for transport

Transit should be anti-exposure, rain, high temperature. Strictly prohibited shipping or transportation with acids, alkalis, oxidants, food and food additives etc. Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

Version: V2.0.0.1 Revision Date: -

15 Regulatory information

International chemical inventory

Component	Α	В	С	D	Е	F	G	Н	I	J	K	L	М
2-methylpropan-1-ol	√	√	√	√	√	√	√	√	√	√	√	√	1
Propan-2-ol	√	√	√	√	√	√	√	√	√	√	√	√	√
Carbon disulphide	1	√	√	1	√	√	√	√	√				√

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZloC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	В	С
2-methylpropan-1-ol	×	×	×
Propan-2-ol	×	×	×
Carbon disulphide	×	×	×

Version: V2.0.0.1 Revision Date: -

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

Component	Α	В	С	D	E	F	G	Н
2-methylpropan-1-ol	×	×	√	√	√	V	√	×
Propan-2-ol	×	×	×	V	√	V	√	×
Carbon disulphide	√	√	√	√	√	V	√	√

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

Note:

- " $\sqrt{}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

16 Other information

Information on revision

Creation Date	2025/10/13
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

| Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG- CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer

DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD_{50}	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC_X	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
Pow	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

Version: V2.0.0.1 Revision Date: -

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.