Safety Data Sheet

Folin phenol B solution

Version: V2.0.0.1

Report No.: BWR0008-2016-MSDS-US

Creation Date: 2025/11/15

Revision Date: -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1	Identification
---	----------------

| Product identifier

Product Name	Folin phenol B solution
Cat No.	BWR0008-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

| Emergency phone number

Emergency phone number	010-58103678
emergency phone number	∥ ∪ IU - 30 IU3070

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Skin corrosion/irritation	Category 1B
Serious eye damage/irritation	Category 1

Label elements

Laborotomonto	
Hazard pictograms	
Signal word	Danger

Hazard statements

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
	- Causes of Camage
Precautionary statements	
Prevention	
P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
◆ Response	
P321	Specific treatment (see related instructions on the label).
P363	Wash contaminated clothing before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse
	affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
_	lenses, if present and easy to do. Continue rinsing.
♦ Storage	
P405	Store locked up.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
Other hazards	
	Not applicable.
	''
lazard description	
 Physical and chemical haz 	ards
	No information available
 Health hazards 	
Inhaled	Corrosive product can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage.
Ingestion	Accidental ingestion of the product may be harmful to the health of the individua
Skin Contact	The product can cause severe skin burns following direct contact with the skin.
Еуе	The product can produce severe chemical burns to the eye following direct contact. If timely and appropriate treatment is not available may cause permane blindness.
 Environmental hazards 	
◆ Environmental hazards	Please refer to 12th chapter of SDS.
◆ Environmental hazards	Please refer to 12th chapter of SDS.

Substance/mixture

Mixture

~	1	12
,	1	17

Component	CAS No.	EC No.	Concentration (wt, %)
Sodium molybdate dihydrate	10102-40-6	600-158-6	10.0005
Phosphoric acid	7664-38-2	231-633-2	8.450
Hydrogen chloride	7647-01-0	231-595-7	11.90
Lithium sulphate	10377-48-7	233-820-4	15.0148
Bromine	7726-95-6	231-778-1	0.078
Disodium wolframate	13472-45-2	236-743-4	2.5020
Water	7732-18-5	231-791-2	52.0547

4 First-aid measures

Description of first aid measures

•	
General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Skin contact	Take off contaminated clothing and shoes immediately. Wash off with plenty of soap and water for at least 15 minutes and consult a physician if feel uncomfortable.
Ingestion	Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.
- 5 Fire-fighting measures

| Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ or water spray; Large fire: dry chemical, CO ₂ , alcohol-resistant foam or water spray; Fire involving tanks, rail tank cars or highway tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of
	water until well after fire is out. Do not get water inside containers.
Unsuitable extinguishing media	No information available.

Specific hazards arising from the substance or mixture

- 1 Fire may produce irritating, poisonous or corrosive gases.
- 2 Development of hazardous combustion gases or vapor possible in the event of fire.

3 May expansion or decompose explosively when heated or involved in fire.

Special protective equipment and precautions for fire-fighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

- 1 Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
 - Do not touch or walk through spilled material.
- 3 Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- 4 Use personal protective equipment, do not breathe gas/mist/vapour/spray.
- Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
- 6 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

2

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

- 1 Do not touch or cross spills.
- It is recommended that emergency personnel wear a self-contained breathing apparatus with positive pressure and wear anti-corrosion clothing.
- 3 Transfer to a tank truck or special collector with a corrosion-resistant pump.
- 4 Do not touch broken containers and spills before putting on appropriate protective clothing.
- 5 Cut off the source of the leak as much as possible.
- 6 Keep leaks in a ventilated place.
- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 8 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
- 9 Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.

7 Handling and storage

Precautions for safe handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

- Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.

- 3 Keep away from heat/sparks/open flames/hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

8 Exposure controls/personal protection

| Control parameters

◆ Occupational exposure limit values

Component	Country/Region	Limit value	- Eight hours	Limit value - Short tern	
		ppm	mg/m³	ppm	mg/m³
Sodium molybdate dihydrate	USA - ACGIH	-	0.5(as Mo, respirable fraction)	-	-
	Finland	-	0.5	-	-
Phosphoric acid	Japan - JSOH(2024–202 5)	-	1	-	-
	Permissible exposure standards for workers in the workplace	-	1	-	2
	Australia	-	1	-	-
	Canada - Ontario	-	1	-	3
	European Union	-	1	-	2
	New Zealand	-	1	-	-
Hydrogen chloride	Japan - JSOH(2024–202 5)	-	-	-	-
	Permissible exposure standards for workers in the workplace	-	-	-	-
	Australia	-	-	5	7.5
	Canada - Ontario	-	-	2	-
	European Union	5	8	10	15
	USA - NIOSH	-	-	5	7
Bromine	Japan - JSOH(2024–202 5)	0.1	0.65	-	-
	Permissible exposure standards for workers in the workplace	0.1	0.66	0.3	1.98
	Australia	0.1	0.66	0.3	2
	European Union	0.1	0.7	-	-
	New Zealand	0.1	0.66	0.3	2
	USA - ACGIH	0.1	-	0.2	-

Disodium wolframate	Permissible	-	1(as W)	-	2(as W)
	exposure				
	standards for				
	workers in the				
	workplace				

| Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

| Personal protection equipment

General requirement		
Eye protection	Must wear appropriate anti-corrosion goggles.	
Hand protection	Must wear acid and alkali resistant chemical protective gloves.	
Respiratory protection	Must wear appropriate personal respiratory protective equipment.	
Skin and body protection	Must wear acid and alkali resistant chemical protective clothing.	

9 Physical and chemical properties and safety characteristics

| Physical and chemical properties

i	
Appearance (physical state, color, etc.)	yellowish-green liquid
Odor	No information available
Odor threshold	No information available
рН	No information available
Melting point/freezing point(°C)	860 (Lithium sulphate)
Initial boiling point and boiling	>35
range(°C)	
Flash point(Closed cup,°C)	No information available
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit : No information available ; Lower limit : No information available
Vapor pressure	No information available
Vapor density(Air = 1)	No information available
Relative density(Water=1)	2.21 (20 °C,Lithium sulphate)
Solubility	342g/L (25 °C,Lithium sulphate)
n-octanol/water partition coefficient	No information available
Auto-ignition temperature(°C)	No information available
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available
n-octanol/water partition coefficient Auto-ignition temperature(°C) Decomposition temperature(°C)	No information available No information available No information available

10 Stability and reactivity

| Stability and reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions	In contact with non-metallic elementals or organics causes a fire or explosion. In contact with magnesium, sodium, potassium, copper and other metals or metal acetylense may cause a fire or explosion. Decomposes if exposed to water, releasing oxygen. In contact with active metals (alkali metals, Na, Ca etc.) causes a reaction and release hydrogen.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Non-metallic elementals, organics and fiber material. Magnesium, sodium, potassium, copper, oxidants, acetylene metal compounds, alcohols, alkanes, hydrogen and water. Water, alkanes, alkynes, aromatic hydrocarbon, halogenated alkanes, oxygen-containing organic compounds, metals, metal hydride, non-metallic hydride, non-metal and metal acetylide, carbonated compounds, azides, nitrogen compounds, caustic, nonmetal oxide and sulfide. Alkali, sodium, calcium, and other active metal, halogen, metal oxide, nonmetal oxide, acyl halide and metal phosphide.
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products
products	should not be produced.

11 Toxicological information

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Lithium sulphate	613mg/kg(Rat)	No information available	No information available
Phosphoric acid	1530mg/kg(Rat)	2740mg/kg(Rabbit)	No information available
Hydrogen chloride	900mg/kg(Rabbit)	No information available	1405ppmV(Rat)
Disodium wolframate	1190mg/kg(Rat)	No information available	No information available
Bromine	2600mg/kg(Rat)	No information available	No information available

Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Sodium molybdate dihydrate	Not Listed	Not Listed	Not Listed
Phosphoric acid	Not Listed	Not Listed	Not Listed
Hydrogen chloride	Category 3	Not Listed	Not Listed
Lithium sulphate	Not Listed	Not Listed	Not Listed
Bromine	Not Listed	Not Listed	Not Listed
Disodium wolframate	Not Listed	Not Listed	Not Listed
Water	Not Listed	Not Listed	Not Listed

Others

Folin phenol B solution			
Skin corrosion/irritation	Causes severe skin burns and eye damage(Category 1B)		
Serious eye damage/irritation	Causes serious eye damage(Category 1)		
Skin sensitization	Based on available data, the classification criteria are not met		
Respiratory sensitization	Based on available data, the classification criteria are not met		
Reproductive toxicity	Based on available data, the classification criteria are not met		
STOT-single exposure	Based on available data, the classification criteria are not met		
STOT-repeated exposure	Based on available data, the classification criteria are not met		
Aspiration hazard	Based on available data, the classification criteria are not met		
Germ cell mutagenicity	Based on available data, the classification criteria are not met		

12 Ecological information

Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Lithium sulphate	LC ₅₀ : 45mg/L (96h)(Fish)	EC ₅₀ : 33.2mg/L	ErC ₅₀ : > 400mg/L
		(48h)(Crustaceans)	(72h)(Algae)
Hydrogen chloride	LC ₅₀ : 20.5mg/L (96h)(Fish)	No information available	No information available
Disodium wolframate	LC ₅₀ : 3710mg/L (96h)(Fish)	EC_{50} : > 163mg/L (48h)(Crustaceans)	ErC ₅₀ : > 17.7mg/L (72h)(Algae)

| Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Lithium sulphate	NOEC: 17.35mg/L(Fish)	No information available	No information available
Disodium wolframate	NOEC : ≥9.8mg/L(Fish)	No information available	No information available

| Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Phosphoric acid	Phosphoric acid High	

| Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Phosphoric acid	Low	Log Kow=-0.7699

Mobility in soil

Component	log Koc	Remark
Phosphoric acid	0.000	

13 Disposal considerations

| Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot
	and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label



IMDG-CODE

UN number	3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard class	None
Packing group	п
Marine pollutant (Yes or no)	No

IATA-DGR

UN number	3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard	None
class	
Packing group	п

UN-ADR

UN number	3264
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard	None
class	
Packing group	п

Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

Others

Precautions for transport

Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

15 Regulatory information

International chemical inventory

Component	Α	В	С	D	Е	F	G	Н	I	J	K	L	М
Sodium molybdate dihydrate	√	×	×	×	√	V	×	√	×	√	×	√	√
Phosphoric acid	√	√	√	√	√	√	√	√	√	√	√	√	√
Hydrogen chloride	√	V	√	√	√								
Lithium sulphate	√	√	√	√	√	√	√	√	√	√	×	√	√
Bromine	√	√	√	√	√	√	√	√	√	√	√	√	√
Disodium wolframate	√	√	√	√	√	√	√	√	√	√	√	√	√
Water	√	√	√	√	√	√	√	√	√	√	√	√	√

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZloC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	Α	В	С
Sodium molybdate dihydrate	×	×	×
Phosphoric acid	×	×	×
Hydrogen chloride	×	×	×
Lithium sulphate	×	×	×
Bromine	×	×	×
Disodium wolframate	×	×	×
Water	×	×	×

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Sodium molybdate dihydrate	×	×	×	×	×	×	×	×
Phosphoric acid	×	×	√	√	√	√	√	×
Hydrogen chloride	√	√	√	√	√	√	√	×
Lithium sulphate	×	×	×	×	×	×	×	×
Bromine	×	√	×	√	√	√	√	×
Disodium wolframate	×	×	×	×	×	×	×	×
Water	×	×	×	×	×	×	×	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

Note:

- " $\sqrt{}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

16 Other information

Information on revision

Creation Date	2025/11/15
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STE	L Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	A Time Weighted Average	IMDG- CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD_{50}	Lethal Dose 50%	NTP	National Toxicology Program
EC_{50}	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC_X	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative

Version: V2.0.0.1 Revision Date: -

Pow Partition coefficient Octanol: Water CMR Carcinogens, mutagens or substances toxic to reproduction BCF Bioconcentration factor RPE Respiratory Protective Equipment ED Endocrine disruptor HCS Hazard Communication Standard

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.