Safety Data Sheet

Non-volatile acids in vinegar

Version: V2.0.0.1

Report No.: BWS0109-2016-MSDS-US

Creation Date: 2025/10/14

Revision Date: -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1 Identification

Product identifier

Product Name	Non-volatile acids in vinegar
Cat No.	BWS0109-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

Recommended use of the product and restrictions on use

_	
Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

| Emergency phone number

Emergency phone number	010-58103678

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Flammable liquids	Category 3
Acute Toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1A
Serious eye damage/irritation	Category 1

Label elements

Hazard pictograms







| Hazard description

Version: V2.0.0.1 Revision Date: -

Physical and chemical hazards

Flammable liquids, its vapor and air mixture can form explosive mixture.

Version: V2.0.0.1 Revision Date: -

Health hazards

Sore throat. Cough. Burning sensation. Headache. Dizziness. Shortness of
breath. Laboured breathing.
Sore throat. Burning sensation. Abdominal pain. Vomiting. Shock or collapse.
Pain. Redness. Skin burns. Blisters.
Redness. Pain. Severe burns. Loss of vision.

Environmental hazards

Please refer to 12th chapter of SDS.

3 Composition/information on ingredients

Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Sulphuric acid	7664-93-9	231-639-5	1.75
Acetic acid	64-19-7	200-580-7	98.25

4 First-aid measures

Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	Rinse with plenty of water (remove contact lenses if easily possible). Refer immediately for medical attention.
Skin contact	Remove contaminated clothes. Rinse skin with plenty of water or shower for at least 15 minutes. Refer immediately for medical attention.
Ingestion	Rinse mouth. Do NOT induce vomiting. If within a few minutes after ingestion, one small glass of water may be given to drinkRefer immediately for medical attention.
Inhalation	Fresh air, rest. Half-upright position. Refer immediately for medical attention.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Small fire: dry chemical, CO ₂ , water spray or alcohol-resistant foam; Large fire:
	water spray, fog or alcohol-resistant foam; Fire involving tanks; Fight fire from

	volucile delas in vinegal	Version : VEISION : VEISION Extension Batte :
		maximum distance or use unmanned master stream devices or monitor nozzles Cool containers with flooding quantities of water until well after fire is out.
Unsu	itable extinguishing media	No information available.
Sı	pecific hazards arising fro	om the substance or mixture
1	Will form explosive mixtures	
2	·	y vent contents through pressure relief valves thereby increasing fire intensity and
_	or vapour concentration.	,
3	Vapours may travel to source	of ignition and flash back.
4	Liquid and vapour are flamm	able.
5	Fire may produce irritating, p	poisonous or corrosive gases.
6	Development of hazardous of	combustion gases or vapor possible in the event of fire.
7	May expansion or decompos	se explosively when heated or involved in fire.
Sn.	oial protoativa aguipman	t and proportions for fire fighters
		t and precautions for fire-fighters
1	protective gear.	ained breathing apparatus (MSHA/NIOSH approved or equivalent) and full
2	Fight fire from a safe distance	e, with adequate cover.
3		ater from contaminating surface water or the ground water system.
	Accidental release me	easures ctive equipment and emergency procedures
1		I contacting with skin and eye.
2		ating to form explosive concentrations.
3	Vapours can accumulate in l	
4	<u> </u>	positive pressure self-contained breathing apparatus. Wear protective and
4	anti-static clothing. Wear che	
5	Fully encapsulating, vapor pr	rotective clothing should be worn for spills and leaks with no fire.
6	Do not touch or walk through	spilled material.
7	Do not touch damaged conta	ainers or spilled material unless wearing appropriate protective clothing.
8	Use personal protective equi	ipment,do not breathe gas/mist/vapour/spray.
9	Ensure adequate ventilation. discharges.	Remove all sources of ignition. Take precautionary measures against static
10	Evacuate personnel to safe a	areas. Keep people away from and upwind of spill/leak.
Fn	vironmental precautions	
1	Prevent further leakage or sp	nillago if safo to do so
		<u> </u>
2	Discharge into the environme	ilit ilitat de avolueu.
Me	thods and materials for co	ontainment and cleaning up
1	It is recommended that emer wear anti-static clothing.	rgency personnel wear positive pressure self-contained breathing apparatus and
2	In case of small amount of s	pillage, use clean non sparking tools to collect absorption materials.
3		pillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to pray mist can reduce evaporation, but can not reduce the flammability of the ce.
4		sing a clean, non-sparking tool.
_		

Cover with anti-solvent foam to reduce evaporation.

Version: V2.0.0.1 Revision Date: -

6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Do not touch or cross spills.
9	It is recommended that emergency personnel wear a self-contained breathing apparatus with positive pressure and wear anti-corrosion clothing.
10	Transfer to a tank truck or special collector with a corrosion-resistant pump.
11	Do not touch broken containers and spills before putting on appropriate protective clothing.
12	Cut off the source of the leak as much as possible.
13	Keep leaks in a ventilated place.
14	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
15	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
16	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
17	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7 Handling and storage

| Precautions for safe handling

1	Avoid inhalation of vapors.
2	Use only non-sparking tools.
3	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
4	Use explosion proof equipment.
5	Handling is performed in a well ventilated place.
6	Wear suitable protective equipment.
7	Avoid contact with skin and eyes.
8	Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

8 Exposure controls/personal protection

| Control parameters

Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m³	ppm	mg/m³
Sulphuric acid	Japan - JSOH(2024–202 5)	-	-	-	-
	Permissible exposure standards for workers in the	-	1	-	2

| Engineering controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

| Personal protection equipment

General requirement	
Eye protection	Must wear appropriate anti-corrosion goggles.
Hand protection	Must wear acid and alkali resistant chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

Physical and chemical properties and safety characteristics

| Physical and chemical properties

Appearance (physical state,	Clear, colorless liquid
color, etc.)	
Odor	No information available
Odor threshold	No information available
рН	2.9 (Acetic acid)
Melting point/freezing point(°C)	16.7 (Acetic acid)
Initial boiling point and boiling range(°C)	118 (Acetic acid)
Flash point(Closed cup,°C)	39 (Acetic acid)
Evaporation rate	No information available

Flammability	No information available
Upper/lower explosive	Upper limit: 17 (Acetic acid); Lower limit: 6.0 (Acetic acid)
limits[%(v/v)]	
Vapor pressure	1.5kPa (20°C ,Acetic acid)
Vapor density(Air = 1)	2.1 (Acetic acid)
Relative density(Water=1)	1.05 (Acetic acid)
Solubility	602900mg/L (25 °C,Acetic acid)
n-octanol/water partition	-0.17 (Acetic acid)
coefficient	
Auto-ignition temperature(°C)	485 (Acetic acid)
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available

10 Stability and reactivity

| Stability and reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions	Flammable, its gas or powder, if in contact with air, may form explosive mixtures.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Metal alkoxides, furfuryl alcohol, acetaldehyde, nitric acid, nitrate, nitrite, oxyacid salt halogen and inorganic peroxide.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 Toxicological information

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Sulphuric acid	2140mg/kg(Rat)	No information available	No information available
Acetic acid	3310mg/kg(Rat)	1130mg/kg(Rabbit)	No information available

| Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Sulphuric acid	Category 1(Remark 1)	Category K	Not Listed
Acetic acid	Not Listed	Not Listed	Not Listed

Remark 1: see Acid mists

Others

Non-volatile acids in vinegar			
Skin corrosion/irritation	Causes severe skin burns and eye damage(Category 1A)		
Serious eye damage/irritation	Causes serious eye damage(Category 1)		
Skin sensitization	Based on available data, the classification criteria are not met		

Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

12 Ecological information

| Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Sulphuric acid	LC ₅₀ : 16mg/L (96h)(Fish)	No information available	No information available
Acetic acid	LC ₅₀ : 300.82mg/L	EC ₅₀ : 65mg/L	No information available
	(96h)(Fish)	(48h)(Crustaceans)	

| Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Acetic acid	NOEC: 34.3 ~57.2mg/L(Fish)	No information available	No information available

| Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Sulphuric acid	Low	Low
Acetic acid	Low	Low

| Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Sulphuric acid	Low	Log Kow=-1.38
Acetic acid	Low	Log Kow=-0.17

Mobility in soil

Component	log Koc	Remark
Sulphuric acid	0.00	20 ℃
Acetic acid	0.06	20 ℃

13 Disposal considerations

| Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and
	regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot
	and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

14 Transport information

Label and Mark

Transporting Label





Version: V2.0.0.1 Revision Date: -

IMDG-CODE

UN number	2789
UN proper shipping name	ACETIC ACID, GLACIAL
Transport hazard class	8
Transport subsidiary hazard	3
class	
Packing group	п
Marine pollutant (Yes or no)	No

IATA-DGR

UN number	2789
UN proper shipping name	ACETIC ACID, GLACIAL
Transport hazard class	8
Transport subsidiary hazard	3
class	
Packing group	П

UN-ADR

UN number	2789
UN proper shipping name	ACETIC ACID, GLACIAL
Transport hazard class	8
Transport subsidiary hazard	3
class	
Packing group	п

Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

Others

Precautions for transport	Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant
	devices, prohibit using mechanical equipment and tools of which easy to produce
	sparks. Transit should be anti-exposure, anti-rain, anti-high temperature.
	Transportation used tank (tank) cars should be grounded chain, tank can be
	installed to reduce the partition hole static electricity shocks. Strictly prohibited
	shipping or transportation with oxidants, acids, food and food additives etc. When

bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

Version: V2.0.0.1 Revision Date: -

15 Regulatory information

International chemical inventory

Component	Α	В	С	D	E	F	G	Н	I	J	K	L	М
Sulphuric acid	√	√	√	√	√	√	√	√	√	√	√	√	√
Acetic acid	√	√	√	√	V	√							

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZIoC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	A	В	С
Sulphuric acid	×	×	×
Acetic acid	×	×	×

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Sulphuric acid	×	√	√	√	√	√	√	×
Acetic acid	×	×	√	√	√	√	√	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

Note:

[&]quot; $\sqrt{}$ " Indicates that the substance included in the regulations.

"x" No data or not included in the regulations.

16 Other information

Information on revision

Creation Date	2025/10/14
Revision Date	-
Reason for revision	-

Version: V2.0.0.1 Revision Date: -

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG-	International Maritime Dangerous Goods CODE
. •	·····o vvolgou/orago	CODE	miomanoma manimo z anigoro do cocao coca
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC ₅₀	Lethal Concentration 50%	NFPA	National Fire Protection Association
LD ₅₀	Lethal Dose 50%	NTP	National Toxicology Program
EC ₅₀	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
EC_X	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
Pow	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.