Safety Data Sheet

Eriochrome Black T

Version: V2.0.0.1

Report No.: BWZ6292-2016-MSDS-US

Creation Date: 2025/10/13

Revision Date: -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

| 1 | Identification |
|---|----------------|
|---|----------------|

| Product identifier

| Product Name | Eriochrome Black T |
|-------------------|--------------------|
| Cat No. | BWZ6292-2016 |
| CAS No. | Not applicable |
| EC No. | Not applicable |
| Molecular Formula | Not applicable |

Recommended use of the product and restrictions on use

| Relevant identified uses | Please consult manufacturer. |
|--------------------------|------------------------------|
| Uses advised against | Please consult manufacturer. |

Details of the supplier of the Safety Data Sheet

| Name of the company | Weiyel Inc |
|------------------------|--|
| Address of the company | Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang |
| | City, Henan Province, China |
| Post code | 465350 |
| Telephone number | 010-58103678 |
| Fax number | 010-84840368 |
| E-mail address | info@weiyel.com |

| Emergency phone number

| Emergency phone number | 010-58103678 |
|------------------------|--------------|

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

| Skin Corrosion/Irritation | Category 2 |
|----------------------------------|------------|
| Sensitization - skin | Category 1 |
| Serious eye damage/irritation | Category 2 |
| Specific target organ toxicity - | Category 3 |
| single exposure; respiratory | |
| tract irritation | |

| Label elements

| Hazard pictograms | |
|-------------------|----------------|
| Signal word | Warning |
| | |

| Hazard statements

| H315 | Causes skin irritation |
|------|-------------------------------------|
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H335 | May cause respiratory irritation |

| Precautionary statements

Prevention

| P261 | Avoid breathing gas/mist/vapour/spray. |
|------|---|
| P264 | Wash hands and other parts of the body (if related) thoroughly after handling. |
| P271 | Use only outdoors or with adequate ventilation. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing |
| | protection. |

Response

| P321 | Specific treatment (see related instructions on the label). |
|----------------|--|
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| | - |

Storage

| P405 | Store locked up. |
|-----------|--|
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Disposal

| P501 Dispose of contents/container in accordance with local/regional/national/international regulations. |
|--|
|--|

Other hazards

Not applicable.

| Hazard description

Physical and chemical hazards

| | No information available |
|----------------------------------|---|
| Health hazards | |
| Inhaled | Cough. Sore throat. |
| Ingestion | Accidental ingestion of the product may be harmful to the health of the individual. |
| Skin Contact | Redness. |
| Eye | Redness. |

Eriochrome Black T Version: V2.0.0.1 Revision Date: -

Environmental hazards

Please refer to 12th chapter of SDS.

3 Composition/information on ingredients

Substance/mixture

Mixture

| Component | CAS No. | EC No. | Concentration (wt, %) |
|--|-----------|-----------|-----------------------|
| Sodium 3-hydroxy-4-[(1-hydroxy-2 -naphthyl)azo]-7-nitronap hthalene-1-sulphonate | 1787-61-7 | 217-250-3 | 0.5 |
| Triethanolamin | 102-71-6 | 203-049-8 | 74.25 |
| Ethanol | 64-17-5 | 200-578-6 | 25.25 |

4 First-aid measures

Description of first aid measures

| General advice | Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance. | |
|--|--|--|
| Eye contact First rinse with plenty of water for several minutes (remove contact lense possible), then take to a doctor. | | |
| Skin contact | Remove contaminated clothes. Rinse and then wash skin with water and soap. | |
| Ingestion | Give one or two glasses of water to drink. | |
| Inhalation | Fresh air, rest. | |
| Protecting of first-aiders | Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination. | |

Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

5 Fire-fighting measures

| Extinguishing media

| Suitable extinguishing media | Use alcohol-resistant foam to extinguish the fire. |
|--------------------------------|---|
| Unsuitable extinguishing media | Use of water spray when fighting fire may be inefficient. |

Specific hazards arising from the substance or mixture

| 1 | Will form explosive mixtures with air. |
|---|---|
| 2 | Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ |
| | or vapour concentration. |
| 3 | Vapours may travel to source of ignition and flash back. |
| 4 | Liquid and vapour are flammable. |

Eriochrome Black T Version: V2.0.0.1 Revision Date:

- 5 Development of hazardous combustion gases or vapor possible in the event of fire.
- 6 May expansion or decompose explosively when heated or involved in fire.

Special protective equipment and precautions for fire-fighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

- 1 Avoid breathing vapours and contacting with skin and eye.
- 2 Beware of vapours accumulating to form explosive concentrations.
- 3 Vapours can accumulate in low areas.
- 4 Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
- 5 Use personal protective equipment, do not breathe gas/mist/vapour/spray.
- 6 Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
- 7 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental precautions

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

- 1 It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
- 2 In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
- In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
- 4 Collect absorbent material using a clean, non-sparking tool.
- 5 Cover with anti-solvent foam to reduce evaporation.
- 6 Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
- 7 Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
- 8 Cut off the source of the leak as much as possible.
- 9 Keep leaks in a ventilated place.
- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 11 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
- Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
- Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7 Handling and storage

Eriochrome Black T Version: V2.0.0.1 Revision Date: -

| Precautions for safe handling

| 1 | Avoid inhalation of vapors. |
|---|---|
| 2 | Use only non-sparking tools. |
| 3 | To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded. |
| 4 | Use explosion proof equipment. |
| 5 | Handling is performed in a well ventilated place. |
| 6 | Wear suitable protective equipment. |
| 7 | Avoid contact with skin and eyes. |
| 8 | Keep away from heat/sparks/open flames/ hot surfaces. |

Conditions for safe storage, including any incompatibilities

| - | |
|---|--|
| 1 | Keep containers tightly closed. |
| 2 | Keep containers in a dry, cool and well-ventilated place. |
| 3 | Keep away from heat/sparks/open flames/hot surfaces. |
| 4 | Store away from incompatible materials and foodstuff containers. |

8 Exposure controls/personal protection

Control parameters

Occupational exposure limit values

| Component | Country/Region | Limit value - Eight hours | | Limit value - Short term | |
|----------------|---|---------------------------|----------------------|--------------------------|-----------------------|
| | | ppm | mg/m³ | ppm | mg/m³ |
| Triethanolamin | Australia | - | 5 | - | - |
| | Canada - Ontario | 0.5 | 3.1 | - | - |
| | New Zealand | - | 5 | - | - |
| | USA - ACGIH | - | 5 | - | - |
| | Austria | 0.8 | 5(inhalable aerosol) | 0.16 | 10(inhalable aerosol) |
| | Belgium | - | 5 | - | - |
| Ethanol | Permissible exposure standards for workers in the workplace | 1000 | 1880 | 1000 | 1880 |
| | Australia | 1000 | 1880 | - | - |
| | Canada - Ontario | - | - | 1000 | - |
| | New Zealand | 1000 | 1880 | - | - |
| | USA - ACGIH | - | - | 1000 | - |
| | USA - NIOSH | 1000 | 1900 | - | - |

| Engineering controls

| 1 | Ensure adequate ventilation, especially in confined areas. |
|---|--|
| 2 | Ensure that eyewash stations and safety showers are close to the workstation location. |
| 3 | Use explosion-proof electrical/ventilating/lighting/equipment. |
| 4 | Set up emergency exit and necessary risk-elimination area. |

| Personal protection equipment

| General requirement | |
|--------------------------|--|
| Eye protection | Must wear appropriate safety goggles. |
| Hand protection | Must wear appropriate chemical protective gloves. |
| Respiratory protection | Must wear appropriate personal respiratory protective equipment. |
| Skin and body protection | Must wear appropriate chemical protective clothing and chemical resistant shoes. |

9 Physical and chemical properties and safety characteristics

| Physical and chemical properties

| 1 2 | |
|---|--|
| Appearance (physical state, | Dark brown to purple-black liquid |
| color, etc.) | |
| Odor | No information available |
| Odor threshold | No information available |
| рН | 10.5 (1% solution, Triethanolamin) |
| Melting point/freezing point(°C) | 21.6 (Triethanolamin) |
| Initial boiling point and boiling | 335.4 (Triethanolamin) |
| range(°C) | |
| Flash point(Closed cup,°C) | 179 (Triethanolamin) |
| Evaporation rate | No information available |
| Flammability | No information available |
| Upper/lower explosive limits[%(v/v)] | Upper limit: 7.2 (Triethanolamin); Lower limit: 3.6 (Triethanolamin) |
| Vapor pressure | <1Pa (25°C,Triethanolamin) |
| Vapor density(Air = 1) | 5.1 (Triethanolamin) |
| Relative density(Water=1) | 1.1 (Triethanolamin) |
| Solubility | Miscible with water (Triethanolamin) |
| n-octanol/water partition | -2.3 (Triethanolamin) |
| coefficient | |
| Auto-ignition temperature(°C) | 324 (Triethanolamin) |
| Decomposition temperature(°C) | No information available |
| Kinematic viscosity | No information available |
| | I . |

10 Stability and reactivity

| Stability and reactivity

| Reactivity | Contact with incompatible substances can cause decomposition or other chemical reactions. |
|------------------------------------|---|
| Chemical stability | Stable under proper operation and storage conditions. |
| Possibility of hazardous reactions | In contact with oxidants causes severe reactions, and may cause a fire or explosion. |
| Teactions | explosion. |
| Conditions to avoid | Incompatible materials, heat, flame and spark. |
| Incompatible materials | Oxidants, alkali metals, alkaline earth metals and aluminum. |
| Hazardous decomposition | Under normal conditions of storage and use, hazardous decomposition products |

products should not be produced.

11 Toxicological information

| Acute toxicity

| Component | LD ₅₀ (oral) | . , , , , | | | | | |
|--|-------------------------|--------------------------|--------------------------|--|--|--|--|
| Sodium 3-hydroxy-4-[(1-hydroxy-2 -naphthyl)azo]-7-nitronap hthalene-1-sulphonate | 17590mg/kg(Rat) | No information available | No information available | | | | |
| Triethanolamin | 5530mg/kg(Rat) | > 22500mg/kg(Rabbit) | No information available | | | | |
| Ethanol | 7060mg/kg(Rat) | No information available | 39mg/L(Mouse) | | | | |

Carcinogenicity

| Component | List of carcinogens by the IARC Monographs | OSHA Carcinogen List | |
|--|--|----------------------|------------|
| Sodium 3-hydroxy-4-[(1-hydroxy-2 -naphthyl)azo]-7-nitronap hthalene-1-sulphonate | Not Listed | Not Listed | Not Listed |
| Triethanolamin | Category 3 | Not Listed | Not Listed |
| Ethanol | Category 1(Remark 1) | Not Listed | Not Listed |

Remark 1: for alcoholic beverages only

Others

| Eriochrome Black T | | | | | |
|-------------------------------|--|--|--|--|--|
| Skin corrosion/irritation | Causes skin irritation(Category 2) | | | | |
| Serious eye damage/irritation | Causes serious eye irritation(Category 2) | | | | |
| Skin sensitization | May cause an allergic skin reaction(Category 1) | | | | |
| Respiratory sensitization | Based on available data, the classification criteria are not met | | | | |
| Reproductive toxicity | Based on available data, the classification criteria are not met | | | | |
| STOT-single exposure | May cause respiratory irritation(Category 3) | | | | |
| STOT-repeated exposure | Based on available data, the classification criteria are not met | | | | |
| Aspiration hazard | Based on available data, the classification criteria are not met | | | | |
| Germ cell mutagenicity | Based on available data, the classification criteria are not met | | | | |

12 Ecological information

| Acute aquatic toxicity

| Component | Fish | Crustaceans | Algae or other aquatic plants |
|----------------|---|---|-------------------------------|
| Triethanolamin | LC ₅₀ : 11800mg/L (96h)(Fish) | EC ₅₀ : 610mg/L (48h)(Crustaceans) | No information available |
| Ethanol | LC ₅₀ : 11200mg/L (96h)(Fish) | EC ₅₀ : 9950mg/L (48h)(Crustaceans) | No information available |

| Chronic aquatic toxicity

Chronic aquatic toxicity

No information available

| Persistence and degradability

| Component | Persistence (water/soil) | Persistence (air) |
|---------------------------|----------------------------|----------------------------|
| Sodium | High | High |
| 3-hydroxy-4-[(1-hydroxy-2 | | |
| -naphthyl)azo]-7-nitronap | | |
| hthalene-1-sulphonate | | |
| Triethanolamin | Low | Low |
| Ethanol | Low(Half-life = 2.17 days) | Low(Half-life = 5.08 days) |

| Bioaccumulative potential

| Component | Bioaccumulative potential | Comments |
|---------------------------|---------------------------|----------------|
| Sodium | Low | Log Kow=3.5624 |
| 3-hydroxy-4-[(1-hydroxy-2 | | |
| -naphthyl)azo]-7-nitronap | | |
| hthalene-1-sulphonate | | |
| Triethanolamin | Low | BCF=4 |
| Ethanol | Low | Log Kow=-0.31 |

Mobility in soil

| Component | log Koc | Remark |
|---------------------------|---------|--------|
| Sodium | 4.761 | |
| 3-hydroxy-4-[(1-hydroxy-2 | | |
| -naphthyl)azo]-7-nitronap | | |
| hthalene-1-sulphonate | | |
| Triethanolamin | 1.000 | |
| Ethanol | 0 | |

13 Disposal considerations

| Disposal considerations

| Waste chemicals | Before disposal should refer to the relevant national and local laws and |
|--------------------------|---|
| | regulation. Recommend the use of incineration disposal. |
| Contaminated packaging | Containers may still present chemical hazard when empty. Keep away from hot |
| | and ignition source of fire. Return to supplier for recycling if possible. |
| Disposal recommendations | Refer to section waste chemicals and contaminated packaging. |

14 Transport information

Label and Mark

Transporting Label



| UN number | 1170 |
|--------------------------------|---|
| UN proper shipping name | ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) |
| Transport hazard class | 3 |
| Transport subsidiary hazard | None |
| class | |
| Packing group | ш |
| Marine pollutant (Yes or no) | No |
| | |

IATA-DGR

| UN number | 1170 |
|-----------------------------|---|
| UN proper shipping name | ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) |
| Transport hazard class | 3 |
| Transport subsidiary hazard | None |
| class | |
| Packing group | ш |

UN-ADR

| UN number | 1170 |
|-----------------------------|--|
| UN proper shipping name | ETHANOL SOLUTION(ETHYL ALCOHOL SOLUTION) |
| Transport hazard class | 3 |
| Transport subsidiary hazard | None |
| class | |
| Packing group | ш |

Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

requirements.

Others

Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature.

Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit

must be placarded and marked in accordance with relevant transporting

15 Regulatory information

Eriochrome Black T Version: V2.0.0.1 Revision Date:

International chemical inventory

| Component | Α | В | С | D | E | F | G | Н | I | J | K | L | М |
|--|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Sodium 3-hydroxy-4-[(1-hydroxy-2 -naphthyl)azo]-7-nitronap hthalene-1-sulphonate | √ | V | V | √ | V | V | V | √ | V | V | √ | √ | √ |
| Triethanolamin | √ | | √ | √ | √ | | √ | √ | √ | √ | √ | √ | √ |
| Ethanol | √ | √ | √ | √ |

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZIoC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)
- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

| Component | Α | В | С |
|--|---|---|---|
| Sodium 3-hydroxy-4-[(1-hydroxy-2 -naphthyl)azo]-7-nitronap hthalene-1-sulphonate | × | × | × |
| Triethanolamin | × | × | × |
| Ethanol | × | × | × |

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- [B] Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

| Component | Α | В | С | D | E | F | G | Н |
|--|---|---|---|---|---|---|---|---|
| Sodium 3-hydroxy-4-[(1-hydroxy- 2-naphthyl)azo]-7-nitron aphthalene-1-sulphonate | × | × | × | × | × | × | × | × |
| Triethanolamin | × | × | × | √ | √ | √ | × | × |
| Ethanol | × | × | × | √ | √ | √ | √ | × |

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

Eriochrome Black T Version: V2.0.0.1 Revision Date:

Note:

- " $\sqrt{}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

16 Other information

Information on revision

| Creation Date | 2025/10/13 |
|---------------------|------------|
| Revision Date | - |
| Reason for revision | - |

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

Abbreviations and acronyms

| CAS | Chemical Abstracts Service | UN | The United Nations | |
|------------------------------|--------------------------------------|-------|---|--|
| PC-STEL | Short term exposure limit | OECD | Organization for Economic Co-operation and Development | |
| PC-TWA Time Weighted Average | Time Weighted Average | IMDG- | International Maritime Dangerous Goods CODE | |
| | Time Weighted Average | CODE | international Marianto Barrigorous Goods GGBL | |
| MAC | Maximum Allowable Concentration | IARC | International Agency for Research on Cancer | |
| DNEL | Derived No Effect Level | ICAO | International Civil Aviation Organization | |
| PNEC | Predicted No Effect Concentration | IATA | International Air Transportation Association | |
| NOEC | No Observed Effect Concentration | ACGIH | American Conference of Governmental Industrial Hygienists | |
| LC ₅₀ | Lethal Concentration 50% | NFPA | National Fire Protection Association | |
| LD ₅₀ | Lethal Dose 50% | NTP | National Toxicology Program | |
| EC ₅₀ | Effective Concentration 50% | PBT | Persistent, Bioaccumulative, Toxic | |
| EC_X | Effective Concentration X% | vPvB | very Persistent, very Bioaccumulative | |
| Pow | Partition coefficient Octanol: Water | CMR | Carcinogens, mutagens or substances toxic to reproduction | |
| BCF | Bioconcentration factor | RPE | Respiratory Protective Equipment | |
| ED | Endocrine disruptor | HCS | Hazard Communication Standard | |

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.