## **Safety Data Sheet**

# Sodium acetate titration solution

Version: V2.0.0.1

Report No.: BWZ8440-2016-MSDS-US

Creation Date: 2025/10/12

Revision Date: -



#### \*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1 Identification

### | Product identifier

Product Name	Sodium acetate titration solution
Cat No.	BWZ8440-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

### Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

### Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

### | Emergency phone number

Г		040 50400070
Emergency	phone number	■ 010-58103678

2 Hazard(s) identification

### Hazard classification according to 29 CFR 1910.1200

Flammable liquids	Category 3
Acute Toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1A
Serious eye damage/irritation	Category 1

#### Label elements

**Hazard pictograms** 







#### | Hazard description

Version: V2.0.0.1 Revision Date: -

### Physical and chemical hazards

Thysical and chemical nazards		
	Flammable liquids, its vapor and air mixture can form explosive mixture.	
<ul><li>Health hazards</li></ul>		
Inhaled	Sore throat. Cough. Burning sensation. Headache. Dizziness. Shortness of breath. Laboured breathing.	
Ingestion	Sore throat. Burning sensation. Abdominal pain. Vomiting. Shock or collapse.	
Skin Contact	Pain. Redness. Skin burns. Blisters.	
Eye	Redness. Pain. Severe burns. Loss of vision.	

Version: V2.0.0.1 Revision Date: -

### Environmental hazards

Please refer to 12th chapter of SDS.

# 3 Composition/information on ingredients

#### Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Acetic acid	64-19-7	200-580-7	98.95
Sodium carbonate	497-19-8	207-838-8	0.51
Acetic anhydride	108-24-7	203-564-8	0.54

# 4 First-aid measures

### Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.	
Eye contact	Rinse with plenty of water (remove contact lenses if easily possible). Refer immediately for medical attention.	
Skin contact	Remove contaminated clothes. Rinse skin with plenty of water or shower for at least 15 minutes. Refer immediately for medical attention.	
Ingestion	Rinse mouth. Do NOT induce vomiting. If within a few minutes after ingestion, one small glass of water may be given to drinkRefer immediately for medical attention.	
Inhalation	Fresh air, rest. Half-upright position. Refer immediately for medical attention.	
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.	

### Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

### Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

# 5 Fire-fighting measures

### Extinguishing media

Suitable extinguishing media | Small fire: dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam; Large fire:

Sodium acetate titration solution	Version: V2.0.0.1 Revision Date: -	
	water spray, fog or alcohol-resistant foam; Fire involving tanks: Fight fire from maximum distance or use unmanned master stream devices or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out.	
Unsuitable extinguishing media	No information available.	
Specific hazards arising from the substance or mixture		
1 Will form explosive mixtures	with air.	

1	Will form explosive mixtures with air.
2	Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/
	or vapour concentration.
3	Vapours may travel to source of ignition and flash back.
1	Liquid and vapour, are flammable

- Liquid and vapour are flammable.
- 5 Fire may produce irritating, poisonous or corrosive gases.
- 6 Development of hazardous combustion gases or vapor possible in the event of fire.
- May expansion or decompose explosively when heated or involved in fire. 7

### Special protective equipment and precautions for fire-fighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

## 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- Avoid breathing vapours and contacting with skin and eye.
- 2 Beware of vapours accumulating to form explosive concentrations.
- 3 Vapours can accumulate in low areas.
- 4 Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
- 5 Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- 6 Do not touch or walk through spilled material.
- 7 Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
- Use personal protective equipment, do not breathe gas/mist/vapour/spray. 8
  - Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
- 10 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### **Environmental precautions**

9

- Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

#### Methods and materials for containment and cleaning up

- It is recommended that emergency personnel wear positive pressure self-contained breathing apparatus and wear anti-static clothing.
- 2 In case of small amount of spillage, use clean non sparking tools to collect absorption materials.
- 3 In case of large amount of spillage, construct cofferdam or dig a hole to collect the spillage. Use foam cover to reduce evaporation. Water spray mist can reduce evaporation, but can not reduce the flammability of the leakage in the restricted space.
- 4 Collect absorbent material using a clean, non-sparking tool.

5	Cover with anti-solvent foam to reduce evaporation.
6	Cover with DRY earth, DRY sand or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain.
7	Water spray reduces evaporation but does not reduce the flammability of spills in confined spaces.
8	Do not touch or cross spills.
9	It is recommended that emergency personnel wear a self-contained breathing apparatus with positive pressure and wear anti-corrosion clothing.
10	Transfer to a tank truck or special collector with a corrosion-resistant pump.
11	Do not touch broken containers and spills before putting on appropriate protective clothing.
12	Cut off the source of the leak as much as possible.
13	Keep leaks in a ventilated place.
14	Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
15	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
16	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.
17	Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

# 7 Handling and storage

### | Precautions for safe handling

1	
1	Avoid inhalation of vapors.
2	Use only non-sparking tools.
3	To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
4	Use explosion proof equipment.
5	Handling is performed in a well ventilated place.
6	Wear suitable protective equipment.
7	Avoid contact with skin and eyes.
8	Keep away from heat/sparks/open flames/ hot surfaces.

## Conditions for safe storage, including any incompatibilities

1	Keep containers tightly closed.
2	Keep containers in a dry, cool and well-ventilated place.
3	Keep away from heat/sparks/open flames/hot surfaces.
4	Store away from incompatible materials and foodstuff containers.

# 8 Exposure controls/personal protection

## | Control parameters

◆Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m³	ppm	mg/m³
Acetic acid	Japan - JSOH(2024–202 5)	10	25	-	-
	Permissible exposure standards for	10	25	15	37.5

	workers in the workplace				
	Australia	10	25	15	37
	Canada - Ontario	10	-	15	-
	European Union	10	25	20	50
	New Zealand	10	25	15	37
Sodium carbonate	Romania	-	1	-	3
Acetic anhydride	Japan - JSOH(2024–202 5)	-	-	-	-
	Permissible exposure standards for workers in the workplace	5	21	10	31.5
	Australia	5	21	-	-
	Canada - Ontario	1	-	3	-
	New Zealand	-	-	5	21
	USA - ACGIH	1	-	3	-

## | Engineering controls

1	Ensure adequate ventilation, especially in confined areas.
2	Ensure that eyewash stations and safety showers are close to the workstation location.
3	Use explosion-proof electrical/ventilating/lighting/equipment.
4	Set up emergency exit and necessary risk-elimination area.

## | Personal protection equipment

General requirement	
Eye protection	Must wear appropriate anti-corrosion goggles.
Hand protection	Must wear acid and alkali resistant chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear anti static chemical protective clothing and anti static shoes.

# 9 Physical and chemical properties and safety characteristics

## | Physical and chemical properties

Appearance (physical state,	colorless liquid
color, etc.)	
Odor	No information available
Odor threshold	No information available
рН	2.9 ( Acetic acid )
Melting point/freezing point(°C)	16.7 ( Acetic acid )
Initial boiling point and boiling	118 ( Acetic acid )
range(°C)	

Flash point(Closed cup,°C)	39 ( Acetic acid )
Evaporation rate	No information available
Flammability	No information available
Upper/lower explosive limits[%(v/v)]	Upper limit: 17 ( Acetic acid ); Lower limit: 6.0 ( Acetic acid )
Vapor pressure	1.5kPa ( 20°C ,Acetic acid )
Vapor density(Air = 1)	2.1 ( Acetic acid )
Relative density(Water=1)	1.05 ( Acetic acid )
Solubility	602900mg/L ( 25 °C,Acetic acid )
n-octanol/water partition coefficient	-0.17 ( Acetic acid )
Auto-ignition temperature(°C)	485 ( Acetic acid )
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available

# 10 Stability and reactivity

### | Stability and reactivity

Committy and to do not try	
Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions	Flammable, its gas or powder, if in contact with air, may form explosive mixtures. May react with strong acids, strong alkalis, strong oxidants or strong reducing agents. Reacts with alkaline metals, alkaline earth metals, ammonia, ammonium ion, methylamine, dimethylamine, trimethylamine, lower aliphatic amines, pyridine or quinoline, decomposes and releases heat.
Conditions to avoid	Incompatible materials, heat, flame and spark.
Incompatible materials	Metal alkoxides, furfuryl alcohol, acetaldehyde, nitric acid, nitrate, nitrite, oxyacid salt halogen and inorganic peroxide. Strong acids, strong alkalis, strong oxidants and strong reducing agents. Alkaline metals, alkaline earth metals, ammonia, ammonium ion, methylamine, dimethylamine, trimethylamine, lower aliphatic amines, pyridine or quinoline, alcohols and oxidants.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# 11 Toxicological information

## Acute toxicity

Component	LD <sub>50</sub> (oral)	LD <sub>50</sub> (dermal)	LC <sub>50</sub> (inhalation,4h)
Acetic anhydride	1780mg/kg(Rat)	4290mg/kg(Rabbit)	4.175mg/L(Rat)
Acetic acid	3310mg/kg(Rat)	1130mg/kg(Rabbit)	No information available
Sodium carbonate	4090mg/kg(Rat)	No information available	No information available

## | Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Acetic acid	Not Listed	Not Listed	Not Listed

Sodium carbonate	Not Listed	Not Listed	Not Listed
Acetic anhydride	Not Listed	Not Listed	Not Listed

### Others

Sodium acetate titration solution				
Skin corrosion/irritation	Causes severe skin burns and eye damage(Category 1A)			
Serious eye damage/irritation	Causes serious eye damage(Category 1)			
Skin sensitization	Based on available data, the classification criteria are not met			
Respiratory sensitization	Based on available data, the classification criteria are not met			
Reproductive toxicity	Based on available data, the classification criteria are not met			
STOT-repeated exposure	Based on available data, the classification criteria are not met			
Aspiration hazard	Based on available data, the classification criteria are not met			
Germ cell mutagenicity	Based on available data, the classification criteria are not met			

# 12 Ecological information

## Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic plants
Acetic anhydride	LC <sub>50</sub> : 300.82mg/L (96h)(Fish)	No information available	No information available
Acetic acid	LC <sub>50</sub> : 300.82mg/L (96h)(Fish)	EC <sub>50</sub> : 65mg/L (48h)(Crustaceans)	No information available
Sodium carbonate	LC <sub>50</sub> :300mg/L (96h)(Fish)	EC <sub>50</sub> : 200mg/L (48h)(Crustaceans)	No information available

## | Chronic aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Acetic anhydride	NOEC: 34.3mg/L(Fish)	No information available	No information available
Acetic acid	NOEC: 34.3	No information available	No information available
	~57.2mg/L(Fish)		

## | Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Acetic acid	Low	Low

## | Bioaccumulative potential

Component	Bioaccumulative potential	Comments			
Acetic acid	Low	Log Kow=-0.17			

## | Mobility in soil

Component	log Koc	Remark			
Acetic acid	0.06	20 ℃			

Acetic anhydride	0.15	

# 13 Disposal considerations

### | Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and regulation. Recommend the use of incineration disposal.
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.

# 14 Transport information

### Label and Mark

Transporting Label





### | IMDG-CODE

UN number	2789
UN proper shipping name	ACETIC ACID, GLACIAL
Transport hazard class	8
Transport subsidiary hazard	3
class	
Packing group	п
Marine pollutant ( Yes or no )	No

### IATA-DGR

UN number	2789
UN proper shipping name	ACETIC ACID, GLACIAL
Transport hazard class	8
Transport subsidiary hazard	3
class	
Packing group	п

## UN-ADR

UN number	2789
UN proper shipping name	ACETIC ACID, GLACIAL
Transport hazard class	8
Transport subsidiary hazard	3
class	
Packing group	П

### Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Version: V2.0.0.1 Revision Date: -Not Available

◆ Transport in bulk in accordance with the IGC Code

Not Available

#### Others

#### **Precautions for transport**

Shipment of the goods vehicle exhaust pipe must be equipped with fire retardant devices, prohibit using mechanical equipment and tools of which easy to produce sparks. Transit should be anti-exposure, anti-rain, anti-high temperature. Transportation used tank (tank) cars should be grounded chain, tank can be installed to reduce the partition hole static electricity shocks. Strictly prohibited shipping or transportation with oxidants, acids, food and food additives etc. When bulk transport, Prohibit the use of cement or wooden boats. Transport vehicles should be equipped with the appropriate variety and quantity of fire equipment and emergency equipment leakage during transport. Before transport, should be preceded by checking whether container integrity, sealing. The transport unit must be placarded and marked in accordance with relevant transporting requirements.

# 15 Regulatory information

### International chemical inventory

Component	Α	В	С	D	Е	F	G	Н	ı	J	K	L	М
Acetic acid	√	√	<b>√</b>	√	<b>√</b>	<b>√</b>	<b>√</b>	√	√	<b>√</b>	<b>√</b>	<b>√</b>	√
Sodium carbonate	√	<b>√</b>	√	<b>√</b>	√	√	<b>√</b>						
Acetic anhydride	√	<b>√</b>	√	<b>√</b>	<b>√</b>								

- (A) China Inventory of Existing Chemical Substances(IECSC)
- (B) European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- (E) New Zealand Inventory of Chemicals(NZIoC)
- (F) Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- (H) Australian. Inventory of Industrial Chemical (AIICS)
- Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- Russia Inventory of Existing Substances (DRAFT)
- [M]Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

#### List of Chemical Substances under International Conventions

Component	Α	В	С
Acetic acid	×	×	×
Sodium carbonate	×	×	×
Acetic anhydride	×	×	×

- (A) The Montreal Protocol on Substances that Deplete the Ozone Layer
- (B) Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

#### US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Acetic acid	×	×	<b>√</b>	<b>√</b>	<b>√</b>	√	√	×
Sodium carbonate	×	×	×	×	×	×	×	×
Acetic anhydride	×	×	√	√	<b>√</b>	√	<b>V</b>	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

#### Note:

- " $\sqrt{}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

# 16 Other information

### Information on revision

Creation Date	2025/10/12
Revision Date	-
Reason for revision	-

#### Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- $\label{lem:local_local$
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

#### Abbreviations and acronyms

CAS	Chemical Abstracts Service	UN	The United Nations
PC-STEL	Short term exposure limit	OECD	Organization for Economic Co-operation and Development
PC-TWA	Time Weighted Average	IMDG- CODE	International Maritime Dangerous Goods CODE
MAC	Maximum Allowable Concentration	IARC	International Agency for Research on Cancer
DNEL	Derived No Effect Level	ICAO	International Civil Aviation Organization
PNEC	Predicted No Effect Concentration	IATA	International Air Transportation Association
NOEC	No Observed Effect Concentration	ACGIH	American Conference of Governmental Industrial Hygienists
LC <sub>50</sub>	Lethal Concentration 50%	NFPA	National Fire Protection Association
$LD_{50}$	Lethal Dose 50%	NTP	National Toxicology Program
EC <sub>50</sub>	Effective Concentration 50%	PBT	Persistent, Bioaccumulative, Toxic
$EC_X$	Effective Concentration X%	vPvB	very Persistent, very Bioaccumulative
Pow	Partition coefficient Octanol: Water	CMR	Carcinogens, mutagens or substances toxic to reproduction
BCF	Bioconcentration factor	RPE	Respiratory Protective Equipment
ED	Endocrine disruptor	HCS	Hazard Communication Standard

#### Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present

state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.