Safety Data Sheet

Sodium hydroxide-ethanol titration solution

Version: V2.0.0.1

Report No.: BWZ8482-2016-MSDS-US

Creation Date: 2025/09/24

Revision Date: -



*Prepared according to American OSHA HCS-2024 (29 CFR 1910.1200)

1	Identification
---	----------------

| Product identifier

Product Name	Sodium hydroxide-ethanol titration solution
Cat No.	BWZ8482-2016
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

Recommended use of the product and restrictions on use

Relevant identified uses	Please consult manufacturer.
Uses advised against	Please consult manufacturer.

Details of the supplier of the Safety Data Sheet

Name of the company	Weiyel Inc
Address of the company	Hedian Light Industrial Park, Chengguan Town, Shangcheng County, Xinyang City, Henan Province, China
Post code	465350
Telephone number	010-58103678
Fax number	010-84840368
E-mail address	info@weiyel.com

| Emergency phone number

Emergency phone number	010-59103679
Emergency phone number	010-58103678

2 Hazard(s) identification

Hazard classification according to 29 CFR 1910.1200

Skin corrosion/irritation	Category 1C
Serious eye damage/irritation	Category 1

Label elements

Laborotomonto	
Hazard pictograms	
Signal word	Danger

| Hazard statements

Sodium hydroxide-ethanol titration solution		Version: V2.0.0.1 Revision Date: -	
	H314	Causes severe skin burns and eye damage	
	H318	Causes serious eye damage	
Precautionary st	atements		
Prevention			

P260	Do not breathe gas/mist/vapour/spray.
P264	Wash hands and other parts of the body (if related) thoroughly after handling.
	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

P321	Specific treatment (see related instructions on the label).
P363	Wash contaminated clothing before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P405	Store locked up.
------	------------------

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.

Other hazards

Not applicable.

No information available

| Hazard description

Physical and chemical hazards

Health hazards	
Inhaled	Cough. Headache. Fatigue. Drowsiness.
Ingestion	Burning sensation. Headache. Confusion. Dizziness. Unconsciousness.
Skin Contact	Dry skin.
Eve	Redness, Pain, Burning.

Environmental hazards

Please refer to 12th chapter of	ΩŤ	SUS
---------------------------------	----	-----

3 Composition/information on ingredients

Substance/mixture

Mixture

Component	CAS No.	EC No.	Concentration (wt, %)
Sodium hydroxide	1310-73-2	215-185-5	0.09

Ethanol	64-17-5	200-578-6	99.91

4 First-aid measures

Description of first aid measures

•	
General advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye contact	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
Skin contact	Remove contaminated clothes. Rinse and then wash skin with water and soap.
Ingestion	Rinse mouth. Refer for medical attention.
Inhalation	Fresh air, rest.
Protecting of first-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

Most important symptoms/effects, acute and delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Indication of any immediate medical attention and special treatment needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

Fire-fighting measures

Extinguishing media

Small fire: dry chemical, CO ₂ or water spray; Large fire: dry chemical, CO ₂ ,
alcohol-resistant foam or water spray; Fire involving tanks, rail tank cars or
highway tanks: Fight fire from maximum distance or use unmanned master
stream devices or monitor nozzles. Cool containers with flooding quantities of
water until well after fire is out. Do not get water inside containers.
No information available.

Specific hazards arising from the substance or mixture

- 1 Fire may produce irritating, poisonous or corrosive gases.
- 2 Development of hazardous combustion gases or vapor possible in the event of fire.
- 3 May expansion or decompose explosively when heated or involved in fire.

Special protective equipment and precautions for fire-fighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.

 Fight fire from a safe distance, with adequate cover.

 Prevent fire extinguishing water from contaminating surface water or the ground water system.
- 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

- 1 Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
 - 2 Do not touch or walk through spilled material.
- 3 Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Use personal protective equipment,do not breathe gas/mist/vapour/spray.
 Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Version: V2.0.0.1 Revision Date: -

Environmental precautions

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

- 1 Do not touch or cross spills.
- It is recommended that emergency personnel wear a self-contained breathing apparatus with positive pressure and wear anti-corrosion clothing.
- 3 Transfer to a tank truck or special collector with a corrosion-resistant pump.
- 4 Do not touch broken containers and spills before putting on appropriate protective clothing.
- 5 Cut off the source of the leak as much as possible.
- 6 Keep leaks in a ventilated place.
- Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 8 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.
- 9 Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container.

7 Handling and storage

Precautions for safe handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.

Conditions for safe storage, including any incompatibilities

- 1 Keep containers tightly closed.
 - 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

8 Exposure controls/personal protection

| Control parameters

Occupational exposure limit values

Component	Country/Region	Limit value - Eight hours		Limit value - Short term	
		ppm	mg/m³	ppm	mg/m³
Sodium hydroxide	Australia	-	-	-	2
	Canada - Ontario	-	-	-	2
	New Zealand	-	-	-	2

	USA - NIOSH	-	-	-	2
	USA - OSHA	-	2	-	-
	Austria	-	2(inhalable aerosol)	-	4(inhalable aerosol)
Ethanol	Australia	1000	1880	-	-
	Canada - Ontario	-	-	1000	-
	New Zealand	1000	1880	-	-
	USA - ACGIH	-	-	1000	-
	USA - NIOSH	1000	1900	-	-
	USA - OSHA	1000	1900	-	-

| Engineering controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

| Personal protection equipment

I a constant be constant a dembassic	
General requirement	
Eye protection	Must wear appropriate anti-corrosion goggles.
Hand protection	Must wear acid and alkali resistant chemical protective gloves.
Respiratory protection	Must wear appropriate personal respiratory protective equipment.
Skin and body protection	Must wear acid and alkali resistant chemical protective clothing.

Physical and chemical properties and safety characteristics

| Physical and chemical properties

Appearance (physical state, color, etc.) Odor No information available No information available PH 14 (50g/L , 20°C,Sodium hydroxide) Melting point/freezing point(°C) Initial boiling point and boiling range(°C) Flash point(Closed cup, °C) Flash point(Closed cup, °C) No information available Evaporation rate No information available Flammability No information available Upper/lower explosive limits[%(v/v)] Vapor pressure < 2kPa (20°C,Sodium hydroxide) Vapor density(Air = 1) Relative density(Water=1) Valor transfer of powder of powder powder No information available of powder in the color of powder of powder of powder in the color of powder of		
Odor threshold No information available PH	Appearance (physical state,	White crystalline solid or powder
Odor threshold pH 14 (50g/L , 20°C,Sodium hydroxide) Melting point/freezing point(°C) Initial boiling point and boiling range(°C) Flash point(Closed cup,°C) No information available Evaporation rate No information available Flammability No information available Upper/lower explosive limits[%(v/v)] Vapor pressure Vapor density(Air = 1) No information available No information available ; Lower limit : No information available Vapor density(Air = 1) No information available	color, etc.)	
Melting point/freezing point(°C) 318 (Sodium hydroxide) 318 (Sodium hydroxide) 318 (Sodium hydroxide) 1388 (Sodium hydroxide	Odor	No information available
Melting point/freezing point(°C) 318 (Sodium hydroxide) Initial boiling point and boiling range(°C) 1388 (Sodium hydroxide) Flash point(Closed cup, °C) No information available Evaporation rate No information available Flammability No information available Upper/lower explosive limits[%(v/v)] Upper limit : No information available ; Lower limit : No information available Vapor pressure < 2kPa (20°C,Sodium hydroxide) Vapor density(Air = 1) No information available	Odor threshold	No information available
Initial boiling point and boiling range(°C) Flash point(Closed cup, °C) No information available Evaporation rate No information available Flammability No information available Upper/lower explosive limits[%(v/v)] Vapor pressure 	рН	14 (50g/L , 20°C,Sodium hydroxide)
range(°C) Flash point(Closed cup, °C) No information available Evaporation rate No information available Flammability Upper/lower explosive limits[%(v/v)] Vapor pressure < 2kPa (20°C,Sodium hydroxide) Vapor density(Air = 1) No information available	Melting point/freezing point(°C)	318 (Sodium hydroxide)
Flash point(Closed cup, °C) No information available Evaporation rate No information available Flammability No information available Upper/lower explosive limits[%(v/v)] Vapor pressure < 2kPa (20°C,Sodium hydroxide) Vapor density(Air = 1) No information available	Initial boiling point and boiling	1388 (Sodium hydroxide)
Evaporation rate No information available Flammability No information available Upper/lower explosive Upper limit: No information available; Lower limit: No information available Vapor pressure < 2kPa (20°C, Sodium hydroxide) Vapor density(Air = 1) No information available	range(°C)	
Flammability No information available Upper/lower explosive limits[%(v/v)] Vapor pressure < 2kPa (20°C,Sodium hydroxide) Vapor density(Air = 1) No information available	Flash point(Closed cup,°C)	No information available
Upper/lower explosive limits[%(v/v)] Vapor pressure < 2kPa (20°C,Sodium hydroxide) Vapor density(Air = 1) Vapor density(Air = 1) Upper limit : No information available ; Lower limit : No information available ; Lower limit : No information available	Evaporation rate	No information available
limits[%(v/v)] Vapor pressure < 2kPa (20°C,Sodium hydroxide)	Flammability	No information available
Vapor pressure < 2kPa (20°C,Sodium hydroxide)	Upper/lower explosive	Upper limit: No information available; Lower limit: No information available
Vapor density(Air = 1) No information available	limits[%(v/v)]	
	Vapor pressure	< 2kPa (20°C,Sodium hydroxide)
Relative density(Water=1) 2.1 (Sodium hydroxide)	Vapor density(Air = 1)	No information available
	Relative density(Water=1)	2.1 (Sodium hydroxide)

Solubility	Miscible with water (Sodium hydroxide)
n-octanol/water partition	No information available
coefficient	
Auto-ignition temperature(°C)	No information available
Decomposition temperature(°C)	No information available
Kinematic viscosity	No information available

10 Stability and reactivity

| Stability and reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical stability	Stable under proper operation and storage conditions.
Possibility of hazardous reactions Conditions to avoid	React violently with acids, phenols or alcohols. In contact with oxidants causes severe reactions, and may cause a fire or explosion. Incompatible materials, heat, flame and spark.
Incompatible materials	Acids, phenols, alcohols and nitro substituted hydrocarbon. Oxidants, alkali metals, alkaline earth metals and aluminum.
Hazardous decomposition	Under normal conditions of storage and use, hazardous decomposition products
products	should not be produced.

11 Toxicological information

Acute toxicity

Component	LD ₅₀ (oral)	LD ₅₀ (dermal)	LC ₅₀ (inhalation,4h)
Ethanol	7060mg/kg(Rat)	No information available	39mg/L(Mouse)

| Carcinogenicity

Component	List of carcinogens by the IARC Monographs	Report on Carcinogens by NTP	OSHA Carcinogen List
Sodium hydroxide	Not Listed	Not Listed	Not Listed
Ethanol	Category 1(Remark 1)	Not Listed	Not Listed

Remark 1: for alcoholic beverages only

Others

Sodium hydroxide-ethanol titration solution	
Skin corrosion/irritation	Causes severe skin burns and eye damage(Category 1C)
Serious eye damage/irritation	Causes serious eye damage(Category 1)
Skin sensitization	Based on available data, the classification criteria are not met
Respiratory sensitization	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
Germ cell mutagenicity	Based on available data, the classification criteria are not met

12 Ecological information

| Acute aquatic toxicity

Component	Fish	Crustaceans	Algae or other aquatic
			plants
Sodium hydroxide	LC ₅₀ :196mg/L (96h)(Fish)	EC ₅₀ : 40.4mg/L (48h)(Crustaceans)	No information available
Ethanol	LC ₅₀ : 11200mg/L (96h)(Fish)	EC_{50} : 9950mg/L (48h)(Crustaceans)	No information available

Version: V2.0.0.1 Revision Date: -

| Chronic aquatic toxicity

Chronic aquatic toxicity No information available

| Persistence and degradability

Component	Persistence (water/soil)	Persistence (air)
Ethanol	Low(Half-life = 2.17 days)	Low(Half-life = 5.08 days)

| Bioaccumulative potential

Component	Bioaccumulative potential	Comments
Ethanol	Low	Log Kow=-0.31

| Mobility in soil

Component	log Koc	Remark
Ethanol	0	

13 Disposal considerations

Disposal considerations

Waste chemicals	Before disposal should refer to the relevant national and local laws and	
	regulation. Recommend the use of incineration disposal.	
Contaminated packaging	Containers may still present chemical hazard when empty. Keep away from hot	
	and ignition source of fire. Return to supplier for recycling if possible.	
Disposal recommendations	Refer to section waste chemicals and contaminated packaging.	

14 Transport information

Label and Mark

Transporting Label



IMDG-CODE

UN number	3267
UN proper shipping name	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard	None
class	

Packing group	ш
Marine pollutant (Yes or no)	No

| IATA-DGR

UN number	3267
UN proper shipping name	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard	None
class	
Packing group	ш

UN-ADR

UN number	3267
UN proper shipping name	CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
Transport hazard class	8
Transport subsidiary hazard	None
class	
Packing group	ш

Transport in bulk according to IMO instruments

◆ Transport in bulk according to Annex II of MARPOL and the IBC code

Not Available

◆ Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Not Available

◆Transport in bulk in accordance with the IGC Code

Not Available

Others

•		
	Precautions for transport	Transport vehicles should be equipped with the appropriate variety and quantity
		of fire equipment and emergency equipment leakage during transport. Before
		transport, should be preceded by checking whether container integrity, sealing.
		The transport unit must be placarded and marked in accordance with relevant
		transporting requirements.

15 Regulatory information

International chemical inventory

Component	Α	В	С	D	E	F	G	Н	I	J	K	L	M
Sodium hydroxide	√	√	√	√	√	√	√	√	V	√	√	√	√
Ethanol	√	1	1	1	1	√	1	1	V	√	√	1	√

- [A] China Inventory of Existing Chemical Substances(IECSC)
- [B] European Inventory of Existing Commercial Chemical Substances(EC inventory)
- [C] United States Toxic Substances Control Act Inventory(TSCA)
- [D] Canadian Domestic Substances List(DSL)
- [E] New Zealand Inventory of Chemicals(NZIoC)
- [F] Philippines Inventory of Chemicals and Chemical Substances(PICCS)
- [G] Korea Existing Chemicals Inventory(KECL)
- [H] Australian. Inventory of Industrial Chemical (AIICS)

- [1] Japan Inventory of Existing & New Chemical Substances(ENCS)
- [J] Thailand Existing Chemicals Inventory(TECI)
- [K] Mexico National Inventory of Chemical Substances (INSQ)
- [L] Russia Inventory of Existing Substances (DRAFT)
- [M] Inventory of Existing Chemical Substances in Taiwan, China (TCSI)

List of Chemical Substances under International Conventions

Component	Α	В	С
Sodium hydroxide	×	×	×
Ethanol	×	×	×

Version: V2.0.0.1 Revision Date: -

- [A] The Montreal Protocol on Substances that Deplete the Ozone Layer
- (B) Stockholm Convention on Persistent Organic Pollutants (POPs)
- [C] Rotterdam Convention on the prior informed consent procedure for certain hazardous chemicals and pesticides in international trade

US chemical inventory

Component	Α	В	С	D	E	F	G	Н
Sodium hydroxide	×	×	√	√	√	√	V	×
Ethanol	×	×	×	√	√	√	V	×

- [A] US Clean Air Act (CAA)- Section 112, Hazardous Air Pollutants
- [B] US SARA 302- Extremely Hazardous Substance List
- [C] US CERCLA- Hazardous Substances List
- [D] US Massachusetts Right-to-Know Substance List
- [E] US New Jersey Right to Know Hazardous Substance List
- [F] US Pennsylvania Right to Know Hazardous Substance List
- [G] US New York City Right-to-Know Hazardous Substance List
- [H] US California Proposition 65 List

Note:

- " $\sqrt{}$ " Indicates that the substance included in the regulations.
- "x" No data or not included in the regulations.

16 Other information

Information on revision

Creation Date	2025/09/24
Revision Date	-
Reason for revision	-

Reference

- [1] IPCS: The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home.
- [2] IARC, website: http://www.iarc.fr/.
- [3] OECD: The Global Portal to Information on Chemical Substances, website: https://www.echemportal.org/echemportal/.
- [4] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple.
- [5] NLM: ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp.
- [6] EPA: Integrated Risk Information System, website: http://cfpub.epa.gov/iris/.
- [7] U.S. Department of Transportation: ERG, website: http://www.phmsa.dot.gov/hazmat/library/erg.
- [8] Germany GESTIS-database on hazard substance, website: http://gestis-en.itrust.de/.

Abbreviations and acronyms

CAS Chemical Abstracts Service UN The United Nations

PC-STEL Short term exposure limit OECD Organization for Economic Co-operation and Development

Disclaimer

This Safety Data Sheet (SDS) was prepared according to OSHA HCS-2024. The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.